Canon

Canon imageFORMULA P-208II Sheet-fed scanner 600 x 600 DPI A4 Black

Brand : Canon   **Product family:** imageFORMULA   **Product code:** 9704B003

Product name : P-208II

600x600DPI, LED, 216x356mm, USB 2.0, 600g, black
Canon imageFORMULA P-208II. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 24 bit. Scanner type: Sheet-fed scanner, Product colour: Black. Sensor type: CIS, Light source: LED, Scan drivers: ISIS, TWAIN. Standard input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Card stock, Plain paper, Post Card(JPN), ISO A-series sizes (A0...A9): A4

Scanning

Maximum scan size *	216 x 356 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	24 bit
Film scanning	✘
Greyscale levels	256
ADF scan speed (b/w, A4)	8 ppm
ADF scan speed (colour, A4)	6 ppm
Duplex ADF scan speed (b/w, A4)	16 ipm
Duplex ADF scan speed (colour, A4)	12 ipm
Black/white scanning colour modes	Grayscale

Design

Scanner type *	Sheet-fed scanner
Product colour *	Black
Built-in display *	✘

Performance

Sensor type *	CIS
Light source	LED
Scan drivers	ISIS, TWAIN

Input capacity

Standard input capacity	1 sheets

Paper handling

Scanning media types supported	Business Card, Card stock, Plain paper, Post Card(JPN)
Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4
Letter	✔

Paper handling

Auto Document Feeder (ADF) media weight	52 - 380 g/m²
Maximum scan area (ADF)	216 x 356 mm
Minimum scan area (ADF)	50.8 x 70 mm

Ports & interfaces

USB port *	✔
USB version	2.0
Standard interfaces	USB 2.0

Power

Power supply type *	USB
Power consumption (typical)	2.5 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.1 W
Current	0.5 A

Weight & dimensions

Width	312.5 mm
Depth	89.5 mm
Height	40 mm
Weight	600 g

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Windows operating systems supported	✔
Mac operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	25 - 80%

Other features

Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	84716070

4528472106366

4053162871083

4528472106359