

Canon imageFORMULA P-208II Arkkisyöttöskanneri 600 x 600 DPI A4 musta

Tuotemerkki : Canon **Tuoteperhe:** imageFORMULA **Tuotekoodi:** 9704B003
Tuotteen nimi : P-208II



Canon imageFORMULA P-208II. Skannauksen enimmäiskoko: 216 x 356 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Tulon värisyvyys: 24 bittiä. Skannerityyppi: Arkkisyöttöskanneri, Tuotteen väri: musta. Anturin tyyppi: CIS, Valonlähde: LED, Skannausajurit: ISIS, TWAIN. Vakiosyöttökapasiteetti (arkkia): 1 arkkiä. Suurin ISO A-luokan paperikoko: A4, Tuetut skannausmediatyyppit: Käyntikortti, Kartonki, Tavallinen paperi, Post Card(JPN), ISO A-sarjan koot (A0...A9): A4

Scanning		Paper handling	
Maximum scan size *	216 x 356 mm	Auto Document Feeder (ADF) media weight	52 - 380 g/m ²
Optical scanning resolution *	600 x 600 DPI	Maximum scan area (ADF)	216 x 356 mm
Colour scanning	✓	Minimum scan area (ADF)	50.8 x 70 mm
Duplex scanning *	✓	Ports & interfaces	
Input colour depth	24 bit	USB port *	✓
Film scanning	✗	USB version	2.0
Greyscale levels	256	Standard interfaces	USB 2.0
ADF scan speed (b/w, A4)	8 ppm	Power	
ADF scan speed (colour, A4)	6 ppm	Power supply type *	USB
Duplex ADF scan speed (b/w, A4)	16 ipm	Power consumption (typical)	2.5 W
Duplex ADF scan speed (colour, A4)	12 ipm	Power consumption (standby)	1.5 W
Black/white scanning colour modes	Grayscale	Power consumption (off)	0.1 W
Design		Current	0.5 A
Scanner type *	Sheet-fed scanner	Weight & dimensions	
Product colour *	Black	Width	312.5 mm
Built-in display *	✗	Depth	89.5 mm
Performance		Height	40 mm
Sensor type *	CIS	Weight	600 g
Light source	LED	Sustainability	
Scan drivers	ISIS, TWAIN	Sustainability certificates	ENERGY STAR
Input capacity		System requirements	
Standard input capacity	1 sheets	Windows operating systems supported	✓
Paper handling		Mac operating systems supported	✓
Scanning media types supported	Business Card, Card stock, Plain paper, Post Card(JPN)	Operational conditions	
Maximum ISO A-series paper size *	A4	Operating temperature (T-T)	10 - 32.5 °C
ISO A-series sizes (A0...A9)	A4	Operating relative humidity (H-H)	25 - 80%
Letter	✓	Other features	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84716070



4528472106366



4053162871083



4528472106359

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.