

## APC AP8853 power distribution unit (PDU) 42 AC outlet(s) 0U Black

Brand : APC

Product code: AP8853

Product name : AP8853

NetShelter Metered Rack PDU, 0U, 1PH, 7.4kW 230V32A, 36 C13 and 6 C19 outlets, IEC 309 2P+E cord APC AP8853. PDU types: Metered, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 42 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 3 m, Certification: RoHS, REACH IEC 60950,VDE. Monitoring: Current, Power, Voltage. AC input frequency: 50 - 60 Hz, Nominal output voltage: 230 V, Load capacity: 7680 VA



| Design                                     |  | Power  |                              |
|--|--|--|------------------------------|
| PDU types *                                | Metered                                      | AC input frequency   | 50 - 60 Hz                   |
| Туре                                       | Single-phase                                 | Nominal output voltage   | 230 V                        |
| Rack capacity *                            | 0U   | Load capacity  | 7680 VA                      |
| Mounting                                   | Vertical                                     | Maximum input current per phase  | 32 A                         |
| Product colour                             | Black  | Maximum total current draw per<br>phase  | 32 A                         |
| Ports & interfaces                         |  | Maximum power  | 7680 W                       |
| AC outlets quantity *<br>Power plug        | 42 AC outlet(s)<br>IEC309                    | Weight & dimensions  |                              |
| AC outlet types *<br>Input connection type | C13 coupler, C19 coupler<br>IEC 309 32A 2P+E | Dimensions (WxDxH)<br>Weight   | 56 x 44 x 1791 mm<br>6.93 kg |
| Output connections                         | 36x IEC 320 C13 6x IEC 320 C19               | Operational conditions   |                              |
| Features                                   |  | Operating temperature (T-T)  | 5 - 45 °C                    |
| Cable length<br>Certification              | 3 m<br>RoHS, REACH IEC 60950,VDE             | Storage temperature (T-T)-25 - 65 °COperating relative humidity (H-H)5 - 95%Common debits of basis in the state of th | 5 - 95%                      |
| Management features                        |  | Storage relative humidity (H-H)  | 5 - 95%                      |
| Monitoring                                 | Current, Power, Voltage                      |  |                              |





731304277019

0731304277019

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.