

APC Rack PDU 2G, Metered-by-Outlet, ZeroU, 16A, 230V, (21) C13 & (3) C19

Brand : APC Product code: AP8459EU3

Product name: Rack PDU 2G, Metered-by-Outlet, ZeroU,

16A, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered-by-Outlet, ZeroU, 16A, 230V, (21) C13 & (3) C19

APC Rack PDU 2G, Metered-by-Outlet, ZeroU, 16A, 230V, (21) C13 & (3) C19:

APC Metered by Outlet Rack Power Distribution Units (PDUs) provide individual outlet power metering to enable energy optimization and circuit protection Current metering provides real-time remote monitoring of connected loads Metered by Outlet Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership Metered by Outlet Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers Users can access and configure Metered by Outlet Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency

Design		Certificates	
PDU types * Rack capacity * Mounting Product colour	Metered, Metered-by-outlet 0U Vertical Black	Compliance certificates Certification	RoHS EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, UL Listed, VCCI Class A, VDE REACH
Ports & interfaces		Operational conditions	
AC outlets quantity * Power plug AC outlet types * Output connections	24 AC outlet(s) IEC309 C13 coupler, C19 coupler 21 x C13 & 3 x C19	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 - 45 °C -25 - 65 °C 5 - 95% 5 - 95%
Features		Operating altitude	0 - 3000 m
LED indicators	/	Non-operating altitude	0 - 15000 m
Cable length	3 m	Weight & dimensions	
Management features		Width	56 mm
Monitoring	Current, Power, Voltage	Depth	51 mm
Power		Height Weight	1829 mm 6.76 kg
Nominal input voltage *	nput frequency 50 - 60 Hz Package imum current * 16 A Package hinal output voltage 230 V Package d capacity 3680 VA Package imum input current per phase 16 A	Packaging data	
AC input frequency Maximum current * Nominal output voltage Load capacity Maximum input current per phase		Package weight Package width Package depth Package height	9.03 kg 163 mm 117 mm 2037 mm
Maximum total current draw per		Logistics data	
phase Maximum power	3680 W	Total carbon footprint (kg of CO2e)	4525.81





731304317562

0731304317562

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.