



APC Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32 power distribution unit (PDU) 4 AC outlet(s) Black



Brand : APC

Product code: AP7586

Product name : Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32

RACK PDU BASIC 2U 32A 230V (4) IEC 309-32


APC Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32 power distribution unit (PDU) 4 AC outlet(s) Black:

The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

APC Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32. PDU types: Basic, Rack capacity: 2U, Mounting: Horizontal. AC outlets quantity: 4 AC outlet(s), Input connection type: Hard Wire 3-wire, Output connections: (4) IEC 309 . Cable length: 8.53 m. Nominal input voltage: 230 V, Nominal output voltage: 230 V, Output voltage: 230 V. Dimensions (WxDxH): 437 x 89 x 89 mm, Weight: 4.09 kg

Design		Power	
PDU types *	Basic	Maximum input current per phase	32 A
Rack capacity *	2U	Maximum total current draw per phase	32 A
Mounting	Horizontal	Maximum power	7680 W
Product colour	Black		
Ports & interfaces		Weight & dimensions	
AC outlets quantity *	4 AC outlet(s)	Dimensions (WxDxH)	437 x 89 x 89 mm
I/O ports	Hard Wire 3-wire (4) IEC 309	Weight	4.09 kg
Input connection type	Hard Wire 3-wire		
Output connections	(4) IEC 309		
Features		Packaging data	
Cable length	8.53 m	Package dimensions (WxDxH)	521 x 521 x 152 mm
		Package weight	5 kg
Power		Operational conditions	
Nominal input voltage *	230 V	Operating temperature (T-T)	0 - 45 °C
Nominal output voltage	230 V	Storage temperature (T-T)	-25 - 65 °C
Output voltage	230 V	Operating relative humidity (H-H)	0 - 45%
Load capacity	7680 VA	Storage relative humidity (H-H)	0 - 95%



0731304224198



731304224198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-NOV-2024. Prints or copies of Information are only valid on the printed Publication date