



## TP-Link Archer MR200 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G Black

**Brand :** TP-Link

**Product code:** ARCHER MR200 V2

**Product name :** Archer MR200

3x 10/100Mbps LAN, 1x 10/100Mbps LAN/WAN, 1x SIM Card, 3G/4G, 802.11ac/a/b/g/n, 433Mbps 5GHz + 300Mbps 2.4GHz

TP-Link Archer MR200. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 433 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G, 2G standards: Edge, GPRS, GSM, 3G standards: DC-HSPA+, HSPA, HSPA+, UMTS. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Data link protocols: IPv4, IPv6



<b>WAN connection</b>		<b>Security</b>	
Ethernet WAN *	✓	IP address filtering	✓
DSL WAN *	✗	<b>Protocols</b>	
SIM card slot *	✓	DHCP client	✓
3G/4G USB modem compatibility *	✗	DHCP server	✓
<b>Wireless LAN features</b>		Universal Plug and Play (UPnP)	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Data link protocols	IPv4, IPv6
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	<b>Design</b>	
WLAN data transfer rate (max) *	433 Mbit/s	Product colour	Black
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	LED indicators	✓
WLAN data transfer rate (first band)	300 Mbit/s	On/off switch	✓
WLAN data transfer rate (second band)	433 Mbit/s	Product type *	Tabletop router
<b>Network</b>		<b>Certificates</b>	
Ethernet LAN *	✓	Certification	CE, FCC, RoHS
Ethernet LAN interface type *	Fast Ethernet	<b>Packaging content</b>	
Ethernet LAN data rates	10,100 Mbit/s	Cables included	LAN (RJ-45)
Cabling technology	10/100Base-T(X)	AC adapter included	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Quick start guide	✓
VPN support	PPTP, L2TP, IPSec	<b>Antenna</b>	
<b>Mobile network</b>		Antenna design *	External
Mobile network generation	4G	Antennas quantity	5
3G	✓	Detachable antenna(s)	✓
4G	✓	<b>Power</b>	
2G standards	Edge, GPRS, GSM	Power source type *	AC
3G standards	DC-HSPA+, HSPA, HSPA+, UMTS	<b>Operational conditions</b>	
4G standard	LTE	Operating temperature (T-T)	0 - 40 °C
GSM bands supported	850,900,1800,1900 MHz	Storage temperature (T-T)	-40 - 70 °C
UMTS bands supported	900,2100 MHz	Operating relative humidity (H-H)	10 - 90%
4G bands supported	800,900,1800,2100,2600 MHz	Storage relative humidity (H-H)	5 - 90%
<b>Ports &amp; interfaces</b>			
Ethernet LAN (RJ-45) ports *	4		
USB port *	✗		
Memory card slot(s)	✗		
DC-in jack	✓		

Management features		System requirements	
Web-based management	✓		
Quality of Service (QoS) support	✓		
Reset button	✓		
Security			
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK		
Firewall	✓		
Stateful Packet Inspection (SPI)	✓		
DoS attack prevention	✓		
Filtering	✓		
MAC address filtering	✓		
		Windows operating systems supported	Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
		Linux operating systems supported	✓
		Mac operating systems supported	✓
Weight & dimensions			
Width		202 mm	
Depth		141 mm	
Height		33.6 mm	
Packaging data			
Micro to standard SIM card adapter			✓
Nano to standard SIM card adapter			✓
Logistics data			
Harmonized System (HS) code		85176990	
Other features			
Input current		1 A	

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date