

TP-Link Archer MR200 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G Black

Brand : TP-Link Product code: ARCHER MR200 V2

Product name: Archer MR200

 $3x\ 10/100 Mbps\ LAN,\ 1x\ 10/100 Mbps\ LAN/WAN,\ 1x\ SIM\ Card,\ 3G/4G,\ 802.11ac/a/b/g/n,\ 433 Mbps\ 5GHz\ +\ 300 Mbps\ 2.4 GHz$

TP-Link Archer MR200. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 433 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G, 2G standards: Edge, GPRS, GSM, 3G standards: DC-HSPA+, HSPA, HSPA+, UMTS. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Data link protocols: IPv4, IPv6





WAN connection		Protocols	
Ethernet WAN * DSL WAN * SIM card slot * 3G/4G USB modem compatibility * Wireless LAN features Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) *	✓ X ✓ X Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 433 Mbit/s 802.11a, Wi-Fi 5 (802.11ac),	DHCP client DHCP server Universal Plug and Play (UPnP) Data link protocols Design Product colour LED indicators On/off switch	IPv4, IPv6 Black
Wi-Fi standards WLAN data transfer rate (first band) WLAN data transfer rate (second band) Network	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Product type * Certificates Certification Packaging content	CE, FCC, RoHS
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates Cabling technology Networking standards VPN support	Fast Ethernet 10,100 Mbit/s 10/100Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n PPTP, L2TP, IPSec	Cables included AC adapter included Quick start guide Antenna Antenna design * Antennas quantity Detachable antenna(s) Transmit power	External 5 0 dBmW
Mobile network Mobile network generation 3G 4G 2G standards 3G standards 4G standard GSM bands supported UMTS bands supported 4G bands supported	4G Edge, GPRS, GSM DC-HSPA+, HSPA, HSPA+, UMTS LTE 850,900,1800,1900 MHz 900,2100 MHz 800,900,1800,2100,2600 MHz	Power Power source type * Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	AC 0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%

Ports & interfaces		System requirements	
Ethernet LAN (RJ-45) ports * USB port * Memory card slot(s) DC-in jack	4 × ×		Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7
Management features			Professional, Windows 7
Web-based management Quality of Service (QoS) support Reset button	* * *		Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro
Security			
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	supported Windows 8.1 Enterprise, W 8.1 Enterprise x64, Windows	x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1
Stateful Packet Inspection (SPI)	✓ ✓		Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business,
DoS attack prevention	v		Windows Vista Business x64, Windows Vista Enterprise, Windows
Filtering	· •		Vista Enterprise x64, Windows Vista
MAC address filtering	✓		Home Basic, Windows Vista Home Basic x64, Windows Vista Home
IP address filtering	•		Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
		Linux operating systems supported	1
		Mac operating systems supported	✓
		Weight & dimensions	
		Width	202 mm
		Depth	141 mm
		Height	33.6 mm
		Packaging data	
		Micro to standard SIM card adapter	
		Nano to standard SIM card adapter	✓
		Logistics data	
		Harmonized System (HS) code	85176990
		Other features	
		Input current	1 A

