



APC Back-UPS UPS-virtalähde Valmiustila (ilman yhteyttä) 0,5 kVA 300 W 4 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BK500EI

Tuotteen nimi : Back-UPS

APC Back-UPS. UPS topologia: Valmiustila (ilman yhteyttä), Kokonaislähtöteho (VA): 0,5 kVA, Lähtöteho: 300 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 7 ah, Akun kapasiteetti: 83 VAH. Kotelo: Tower, Tuotteen väri: Beige, Johdon pituus: 1,83 m. Tuotteen leveys: 91 mm, Tuotteen syvyys: 284 mm, Tuotteen korkeus: 165 mm



Features		Design	
UPS topology *	Standby (Offline)	Product colour *	Beige
Output power capacity *	0.5 kVA	LED indicators	Battery replacement
Output power *	300 W	Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, REACH
Waveform *	Sine		
Input operation voltage (min) *	160 V		
Input operation voltage (max) *	300 V		
Input frequency *	50/60 Hz		
Output frequency regulation	47 - 63 Hz		
Surge energy rating	310 J		
Hold time (min)	6 ms		
Hold time (max)	10 ms		
Efficiency	99%		
Noise level	40 dB		
Surge protection	✓		
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Telephone		
Power protection features	Overload		
Audible alarm(s)	✓		
Audible alarm modes	Low battery alarm, Overload alarm		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	4 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
Number of output IEC jumpers	2	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	ENERGY STAR, Green Premium
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	91 mm
		Depth	284 mm
		Height	165 mm
		Weight	6.32 kg
		Package width	241 mm
		Package depth	368 mm
		Package height	178 mm
		Package weight	7.05 kg

Ports & interfaces		Packaging data	
USB port	✓	Cables included	Phone (RJ-11), USB cable
Battery		Quick installation guide	✓
Battery technology	Sealed Lead Acid (VRLA)	Warranty card	✓
Battery capacity	7 Ah	Software CD	✓
Battery capacity	83 VAh	Bundled software	PowerChute Personal Edition
Battery voltage	12 V	Logistics data	
Typical backup time at full load	3.8 min	Products per pallet	48 pc(s)
Typical backup time at half load	13.8 min	Harmonized System (HS) code	85078000
Battery life (max)	6 year(s)	Products per master (outer) case	1 pc(s)
Battery recharge time	8 h	Other features	
Automatic battery test	✓	Nominal output voltage	230 V
Design		Nominal input voltage	230 V
Form factor *	Tower	Filtering	✓
Cable length	1.83 m	Packaging content	Detachable 1.2m IEC power cord Detachable 1.8 m IEC power cord



0731304016359



731304016359

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.