

Epson LX-1350 dot matrix printer 240 x 144 DPI Colour 357 cps

Brand : Epson

Product code: C11CD24301

Product name : LX-1350

Impact dot matrix, 9 pins, 136 columns, 9 Needles, 240 x 144 DPI, USB 2.0, RS-232, 33 Watt, 6.6 kg
 Epson LX-1350. Maximum print speed: 357 cps, Maximum resolution: 240 x 144 DPI, Maximum print speed (draft): 312 cps. Maximum print size: A3 (297 x 420 mm), Paper tray media types: Envelopes, Labels, Roll, Continuous paper thickness range: 0.065 - 0.39 mm. Product colour: Black, Grey, Buffer size: 128 KB, Sound pressure level (printing): 54 dB. Standard interfaces: RS-232, USB 2.0. Print head: 9-pin, Print direction: Bidirectional, Print head life: 400 million characters



Printing		Operational conditions	
Maximum resolution *	240 x 144 DPI	Storage relative humidity (H-H)	10 - 80%
Maximum printing width (columns) *	136	System requirements	
Colour *	✓	Windows operating systems supported	Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP
Maximum print speed *	357 cps	Server operating systems supported	Windows Server 2008 R2
Maximum print speed (draft)	312 cps	Bundled software	Epson Status Monitor
Character pitch	10,12 cpi	Weight & dimensions	
Maximum number of copies	5 copies	Width	546 mm
Built-in barcodes	Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E	Depth	275 mm
Print speed	NLQ: 12 cpi: 78 chars/s, 10 cpi: 65 chars/s, Draft: 12 cpi: 312 chars/s, 10 cpi: 260 chars/s, HighSpeed-Draft: 12 cpi: 357 chars/s, 10 cpi: 347 chars/s	Height	164 mm
Paper handling		Weight	6.6 kg
Maximum print size	A3 (297 x 420 mm)	Packaging data	
Paper tray media types	Envelopes, Labels, Roll	Quantity per pack	1 pc(s)
Continuous paper thickness range	0.065 - 0.39 mm	Package width	220 mm
Single sheet thickness range	0.065 - 0.14 mm	Package depth	640 mm
Features		Package height	380 mm
Product colour *	Black, Grey	Package weight	7.73 g
Buffer size *	128 KB	Other features	
Sound pressure level (printing) *	54 dB	Standard media sizes	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes
Page description languages *	ESC P, PPDS	Connectivity technology	Wired
Country of origin	Indonesia	Print technology	Dot matrix
Ports & interfaces		Box contents	Driver and utilities (CD), Main unit, Power cable, Ribbon, Setup guide, Software (CD), User manual (CD), Warranty document
Standard interfaces *	RS-232, USB 2.0	Needles	9 Needles
Endurance		Logistics data	
Print head *	9-pin	Products per pallet	27 pc(s)
Print direction	Bidirectional	Pallet gross length	120 cm
Print head life	400 million characters	Pallet gross width	80 cm
Ribbon life (black, draft)	4 million characters	Pallet gross height	2.15 m
Mean time between failures (MTBF)	10000 h	Products per pallet layer	3 pc(s)
Power		Products per pallet layer (UK)	3 pc(s)
Power consumption (typical)	33 W	Products per pallet (UK)	27 pc(s)
AC input voltage	220 - 240 V		

Operational conditions		Logistics data	
Operating temperature (T-T)	5 - 35 °C	Pallet length (UK)	120 cm
Storage temperature (T-T)	5 - 35 °C	Pallet width (UK)	100 cm
Operating relative humidity (H-H)	10 - 80%	Pallet height (UK)	2.15 m
		Harmonized System (HS) code	84433210



8715946540504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date