

## Epson TM-U220A (057): Serial, PS, EDG

**Brand :** Epson

**Product code:** C31C513057

**Product name :** Epson TM-U220A (057): Serial, PS, EDG

TM-U220A Grey/ RS-232/ Take up/ Automatic cutter

[Epson TM-U220A \(057\): Serial, PS, EDG:](#)

Epson's TM-U220 impact printers are compact, reliable and optimized for high-speed throughput. They offer all the easy-to-use features important to the retail, restaurant and hospitality industries and two-color printing to highlight special offers, kitchen orders and impactful logos. In addition, the TM-U220 printers have been designed to be 100% compatible with existing systems that currently use a TM-U200 printer.

### Product Features:

- Print speeds up to 4.6 lines-per-second.
- Easy to operate.
- Increased data buffer at 4KB.
- 30% faster than the TM-U200 series.
- Drop-in paper loading.
- Two-color black and red receipt and order printing.
- Right-side-up printing for kitchen orders.
- Flexible paper widths.
- Wall mounting option - allows the Epson TM-U220 to be mounted on the wall, ideal for hospitality applications.



<b>Printing</b>		<b>Weight &amp; dimensions</b>	
Colour	×	Depth	248 mm
Print technology *	Dot matrix	Height	139 mm
Type *	POS printer	Weight	2.7 kg
<b>Paper handling</b>		<b>Packaging data</b>	
Printing media thickness	0.06/0.085 µm	Quantity per pack	1 pc(s)
Maximum printing width	4.2 cm	Package width	240 mm
<b>Ports &amp; interfaces</b>		Package depth	375 mm
Connectivity technology *	Wired	Package height	250 mm
<b>Network</b>		Package weight	4.3 kg
Ethernet LAN *	×	<b>Logistics data</b>	
Wi-Fi *	×	Harmonized System (HS) code	84433210
<b>Features</b>		Products per pallet	56 pc(s)
Mean time between failures (MTBF)	180000 h	Products per pallet layer	8 pc(s)
Standard media sizes	63 / 57 /47 mm	Pallet gross width	120 cm
Country of origin	China	Pallet gross height	100 cm
Ribbon life	3 million characters	Products per pallet (UK)	84 pc(s)
Safety	UL, CSA, TÜV (EN60950)	Products per pallet layer (UK)	12 pc(s)
<b>Power</b>		Pallet length (UK)	2.25 m
Power consumption (printing)	31 W	<b>Other features</b>	
<b>System requirements</b>		Dimensions (WxDxH)	160 x 286 x 157.5 mm
Compatible operating systems	Windows 2000, XP, Vista	Buffer size	4 KB
<b>Weight &amp; dimensions</b>		Electromagnetic compatibility	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Width	160 mm		



8715946191041

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date