Epson TM-P80 (652): Receipt, NFC, BT, PS, EU

Tuotemerkki : Epson Tuotekoodi: C31CD70652

Tuotteen nimi: TM-P80 (652): Receipt, NFC, BT, PS, EU

Epson TM-P80 (652): Receipt, NFC, BT, PS, EU. Tulostustekniikka: Suoralämpö, Malli: Maksupäätetulostin, Suurin resoluutio: 203 x 203 DPI. Tulostusmateriaalin paksuus: 50 - 80 µm, Suurin rullan halkaisija: 5,1 cm, Tuetut paperin leveydet: 79.5 mm. Yhteysteknologia: Langallinen & langaton, USB-liitin: Mini-USB Type-B, Vakioliitännät: Bluetooth, USB 2.0. Äänenpainetaso (tulostus): 53 dB, Keskimääräinen vikaantumisaika: 120000 h, Tulostuspään ikä: 50 km. Tuotteen väri: musta





Printing		Operational conditions	
Print speed Print speed (receipt) Character sets Print technology *	203 x 203 DPI 100 mm/sec 100 mm/sec ANK Direct thermal POS printer	Operating relative humidity (H-H)	10 - 90%
		Weight & dimensions	
		Width Depth Height Weight	110 mm 140 mm 64 mm 500 g
Paper handling		Packaging data	
Printing media thickness Maximum roll diameter Supported paper width Media thickness Ports & interfaces USB port *	50 - 80 μm 5.1 cm 79.5 mm 0.05 - 0.08 mm	Cables included Quantity per pack Package width Package depth Package height Package weight	AC, USB 1 pc(s) 190 mm 235 mm 172 mm 1.6 kg
USB 2.0 ports quantity	1	Logistics data	
USB connector Bluetooth Connectivity technology * Standard interfaces	Mini-USB Type-B ✓ Wired & Wireless Bluetooth, USB 2.0	Pallet weight (UK) Harmonized System (HS) code Products per pallet Products per pallet layer	0 g 84433210 160 pc(s) 32 pc(s)
Network		Pallet gross width	80 cm
Ethernet LAN * Wi-Fi *	x x	Pallet gross length 120 Pallet gross height 95 c	120 cm 95 cm 0 g
Features		Products per pallet (UK)	240 pc(s)
Sound pressure level (printing) Mean time between failures (MTBF) Print head life Country of origin	53 dB 120000 h 50 km China	Products per pallet layer (UK) Pallet width (UK) Pallet length (UK) Pallet height (UK)	48 pc(s) 100 cm 120 cm 95 cm
Mounting position	Horizontal/Vertical	Technical details	
Safety Certification	UL, CSA FCC-Class A, CE	Font styles Lifetime	ANK 10000000 lines
Design Product colour *	Black	Paper size roll paper	79.50 ± 0.50 (W) mm x dia 51.00 mm
		Other features	
		Buffer size	0.128 KB

Power		Other features	
Power plug type Battery life (max)	Type C 46 h	Mean cycles between failures (MCBF)	16000000
Operational conditions		Print head life	50 km - 100.000.000 Impulse
Storage temperature (T-T)	-25 - 70 °C		



8715946602615

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.