## Epson TM-T70II (032) 180 x 180 DPI Langallinen Thermal Maksupäätetulostin

Tuotemerkki : Epson

Tuotekoodi: C31CD38032

Tuotteen nimi : TM-T70II (032)

Epson TM-T70II (032). Tulostustekniikka: Thermal, Malli: Maksupäätetulostin, Suurin resoluutio: 180 x 180 DPI. Suurin rullan halkaisija: 8,3 cm, Tuetut paperin leveydet: 80 mm. Yhteysteknologia: Langallinen, USB-liitin: USB B-tyyppi, Vakioliitännät: Sarja. Äänenpainetaso (tulostus): 55 dB, Keskimääräinen vikaantumisaika: 360000 h, Alkuperämaa: Kiina. Tuotteen väri: musta



| <b>B</b> datta                    |                             |  |                      |
|-----------------------------------|-----------------------------|--|----------------------|
| Printing                          |                             | Operational conditions   | 10.000/              |
| Maximum resolution<br>Print speed | 180 x 180 DPI<br>250 mm/sec | Operating relative humidity (H-H)<br>Storage relative humidity (H-H) | 10 - 90%<br>10 - 90% |
| Print technology *                | Thermal                     | 5  | 10 - 30 /0           |
| Type *                            | POS printer                 | Weight & dimensions  | 125                  |
| Paper handling                    |                             | Width<br>Depth   | 125 mm<br>194 mm     |
| Maximum roll diameter             | 8.3 cm                      | Height   | 114 mm               |
| Supported paper width             | 80 mm                       | Weight   | 1.7 kg               |
| Ports & interfaces                |                             | Packaging data   |                      |
| USB port *                        | 1                           | Cables included  | AC                   |
| USB 2.0 ports quantity            | 1                           | Quantity per pack  | 1 pc(s)              |
| USB connector                     | USB Type-B                  | Package width  | 192 mm               |
| Serial interface *                | 1                           | Package depth  | 253 mm               |
| Bluetooth                         | ×                           | Package height   | 240 mm               |
| Connectivity technology *         | Wired                       | Package weight   | 2.56 kg              |
| Serial ports quantity             | 1                           | Print technology   |                      |
| Standard interfaces               | Serial                      | Column capacity  | 80 mm, 56 / 42       |
| Network                           |                             | Logistics data   |                      |
| Ethernet LAN *                    | ×                           | Harmonized System (HS) code  | 84433210             |
| Wi-Fi *                           | ×                           | Products per pallet  | 112 pc(s)            |
| Features                          |                             | Products per pallet layer  | 16 pc(s)             |
| Sound pressure level (printing)   | 55 dB                       | Pallet gross width<br>Pallet gross length                            | 80 cm<br>120 cm      |
| Mean time between failures (MTBF) | 360000 h                    | Pallet gross height  | 181.6 cm             |
| Country of origin                 | China                       | Products per pallet (UK)   | 168 pc(s)            |
| Safety                            | TÜV, GOST-R                 | Products per pallet layer (UK)                                       | 24 pc(s)             |
| Certification                     | CE, EN55022 Class A         | Pallet width (UK)  | 100 cm               |
| Design                            |                             | Pallet length (UK)   | 120 cm               |
| Product colour *                  | Black                       | Pallet height (UK)   | 181.6 cm             |
| Power                             |                             | Other features   |                      |
| Power consumption                 | 100 mA                      | Dimensions (WxDxH)   | 125 x 194 x 114 mm   |
| Operational conditions            |                             | Buffer size  | 4 KB                 |
| Operating temperature (T-T)       | 5 - 40 °C                   |  |                      |
| Storage temperature (T-T)         | -10 - 50 °C                 |  |                      |





5054484562894

8715946530611

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.