



ATEN CS1644A-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CS1644A-AT-G

Tuotteen nimi : CS1644A-AT-G



ATEN CS1644A-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-I. HD-tyyppi: WQXGA, Enimmäiserottelutarkkuus: 2560 x 1600 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Voimanlähde: DC, Tulojännite: 5.3 V, Virrankulutus: 12,19 W. Muu käyttöjärjestelmätuki: FreeBSD



Ports & interfaces		System requirements	
Number of computers controlled *	4	Windows operating systems supported	✓
Keyboard port type *	USB	Linux operating systems supported	✓
Mouse port type *	USB	Mac operating systems supported	✓
Video port type *	DVI-I	Other operating systems supported	FreeBSD
DVI-I ports quantity	10	Sustainability	
USB 2.0 Type-B ports quantity	4	Compliance certificates	RoHS
Console ports *	3.5mm headphone, 3.5mm mic, DVI-I, USB A	Operational conditions	
Console USB ports quantity	2	Operating temperature (T-T)	0 - 50 °C
USB hub	✓	Storage temperature (T-T)	-20 - 60 °C
USB 2.0 Type-A hub ports quantity	2	Operating relative humidity (H-H)	0 - 80%
USB connector type	USB Type-A	Weight & dimensions	
Audio connections	✓	Width	437.2 mm
Headphone outputs	4	Depth	159.8 mm
Number of microphone inputs	4	Height	44 mm
DC-in jack	✓	Weight	2.32 kg
Network		Packaging data	
Ethernet LAN (RJ-45) ports	1	Package width	208 mm
Performance		Package depth	560 mm
HD type *	WQXGA	Package height	240 mm
Maximum resolution *	2560 x 1600 pixels	Package weight	5.5 kg
Video bandwidth	60 Hz	Packaging content	
Scan interval	1,99 s	Cables included	KVM
HDCP	✓	Manual	✓
Design		Logistics data	
Rack mounting *	✓	Master (outer) case net weight	13.5 kg
Rack capacity	1U	Harmonized System (HS) code	85176200
Product colour *	Black	Master (outer) case width	573 mm
Housing material	Metal, Plastic	Master (outer) case length	642 mm
Push button	✓	Master (outer) case height	264 mm
Hot keys	✓	Master (outer) case gross weight	17.9 kg
		Products per master (outer) case	3 pc(s)

Display

Built-in display *	×
--------------------	---

Power

Power source	DC
Input voltage	5.3 V
Power consumption (typical)	12.19 W



4710423779686

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.