

A-80 SERIES

CTG-650C // MODULAR // 650WATT



Product: PSU

Form factor: PSII

Color: silver

this popular PSU series is now extended by new models featuring cable management. With many awards granted, these PSUs are perfectly suited for cost aware users, who pay attention to both good price and high efficiency.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: > 85%

Dimensions (DxWxH): 140 mm x 150 mm x 87 mm

PCF: Active PFC (0,9)

Fan: 120mm silent fan

Connectors

| 24PIN | 8PIN EPS | 4PIN 12V | SATA | Molex | Floppy | 8PIN PCIe (6+2) | 6PIN PCIe |
|-------|----------|----------|------|-------|--------|-----------------|-----------|
| 1 | 1 | 0 | 6 | 4 | 2 | 2 | 0 |

DC Output / AC Input

| AC INPUT: 230V / 6A FREQUENCY: 50 HZ MAX. LOAD: 650W | DC OUTPUT | | | | | | | | |
|--|-----------|-------|-------|-------|-------|-------|------|--------------|-----------|
| | +5V | +3,3V | +12V1 | +12V2 | +12V3 | +12V4 | P.F. | -12V | +5VSB |
| | 22A | 22A | 30A | 30A | N/A | N/A | >0,9 | 0,3A 3,6W | 3A 15W |
| | 130W | | 552W | | N/A | | | | |

Security:

UVP; OVP; SCP; OPP; AFC; SIP
MBTF (Mean Time Between Failure): >50.000h

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.