

## Chieftec CTG-650C virtalähdeyksikkö 650 W 24-pin ATX ATX musta

**Tuotemerkki :** Chieftec

**Tuotekoodi:** CTG-650C

**Tuotteen nimi :** CTG-650C

Chieftec CTG-650C. Kokonaisteho: 650 W, AC-syöttöjännite: 230 V, AC-syöttötaajuus: 50 Hz. Emolevyn virtaliitin: 24-pin ATX, Kaapelointityyppi: Puolimodulaarinen. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 87 mm



Power		Ports & interfaces	
Total power *	650 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	230 V	CPU P4 connector (4-pin)	1
AC input frequency	50 Hz	Floppy drive power connector	2
Input current	6 A	CPU power connectors (8-pin)	1
Maximum input current (@110V)	+12V1,+12V2,+3.3V,+5V,+5Vsb,-12V	Cabling type	Semi-Modular
Power factor	0.9	Performance	
Power Factor Correction (PFC) type	Active	80 PLUS certification *	80 PLUS
Combined power (+3.3V)	130 W	Purpose *	PC
Combined power (+12V)	552 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5V)	130 W	ATX version	2.3
Combined power (-12V)	3.6 W	Mean time between failures (MTBF)	100000 h
Combined power (+5Vsb)	15 W	Certification	CE, CB, FCC
Max output current (+3.3V)	22 A	Design	
Max output current (+12V1)	300 A	Product colour	Black
Max output current (+12V2)	30 A	Cooling type	Active
Max output current (+5V)	22 A	Fan diameter	12 cm
Max output current (-12V)	0.3 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	Fan location	Top
Efficiency	85%	Weight & dimensions	
Power protection features	Over current, Over voltage, Overheating, Overload, Short circuit, Under current, Under voltage	Width	150 mm
Ports & interfaces		Depth	140 mm
Motherboard power connector *	24-pin ATX	Height	87 mm
Number of SATA power connectors	6	Packaging data	
Peripheral (Molex) power connectors (4-pin) *	4	Package type	Box
EPS power connector (8-pin)	✓	Technical details	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84733020



4710713239371

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.