D-Link

D-Link DGS-1510-28P network switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : D-Link Product code: DGS-1510-28P

Product name: DGS-1510-28P

POE, 28x10/100/1G, 2 x 10G SFP+, 2 x SFP SmartPro Stackable Switch


D-Link DGS-1510-28P. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 92 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE.... Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting



0	•	

Management features		Performance		
Switch type *	Managed	Noise level	46.4 dB	
Switch layer	L3	Power		
Quality of Service (QoS) support	1	AC input voltage	100 - 240 V	
Web-based management System event log	1	AC input frequency	50 - 60 Hz	
-	•	Power consumption (typical)	238.7 W	
Ports & interfaces		Power over Ethernet (PoE)		
Basic switching RJ-45 Ethernet ports quantity *	24	Power over Ethernet (PoE) *	✓	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) ports quantity	24	
SFP module slots quantity	2	Total Power over Ethernet (PoE)	193 W	
SFP+ module slots quantity	2	budget		
Power connector	DC-in jack	Operational conditions		
Network		Operating temperature (T-T)	-5 - 50 °C	
	IEEE 802.1D, IEEE 802.1p, IEEE	Storage temperature (T-T)	-20 - 70 °C	
Networking standards *	802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE	Operating relative humidity (H-H)	0 - 95% 0 - 95%	
-	802.3ae, IEEE 802.3u, IEEE 802.3x	Storage relative humidity (H-H) Heat dissipation	813.967 BTU/h	
10G support *	✓	·	615.567 816/11	
Cable types supported	Cat5, Cat5e	Weight & dimensions		
Port mirroring	1	Width	440 mm	
Full duplex	✓	Depth	250 mm 44 mm	
Flow control support	V	Height Weight	2.54 kg	
Link aggregation	V		2.54 kg	
Broadcast storm control Auto MDI/MDI-X	4	Packaging content		
Head-of-line (HOL) blocking	1	Manual	✓	
Auto-negotiation	1	Packaging data		
MAC address auto-learning		Package width	348 mm	
supported	4	Package depth	511 mm	
VLAN support	1	Package height	91 mm	
Data transmission		Package weight	4 kg	
Switching capacity *	92 Gbit/s	Technical details		
Forwarding rate	68.45 Mpps	Shipping (inner) case height	38.3 cm	
MAC address table *	16000 entries	Shipping (inner) case width	29.6 cm	
Store-and-forward	1	Shipping (inner) case length	52.9 cm	
Number of static routes	512	Shipping (inner) case net weight	9.27 kg	
Jumbo frames support	√	Products per shipping (inner) case	3 pc(s)	
Packet buffer memory	1.5 MB	Pallet gross weight (air) Master (outer) cases per pallet (air)	533.9 kg	
Security		Master (outer) cases per pallet (air) Products per pallet (air)	40 pc(s) 120 pc(s)	
DHCP features	DHCP server, DHCP client	Pallet gross length	110 cm	

Security		Technical details	
Access Control List (ACL)	✓	Pallet gross width	120 cm
IGMP snooping	✓	Pallet height (air)	2.05 m
MAC address filtering	✓	Pallet gross weight (sea)	533.9 kg
Static port security	✓	Master (outer) cases per pallet (sea)	40 pc(s)
SSH/SSL support	✓	Products per pallet (sea)	120 pc(s)
Multicast features		Pallet height (sea)	2.05 m
Multicast support	1	Shipping (inner) case gross weight	12.9 kg
	•	Certificates	
Design		Certification	CE, FCC, C-Tick, VCCI, BSMI, CCC
Rack mounting *	✓	Lauistica data	
Stackable *	✓	Logistics data	
Product colour	Black	Harmonized System (HS) code	85176990
LED indicators	Activity, Link, PoE, Power		
Number of fans	2 fan(s)		
Safety	cUL, CB		
Performance			
Physical stacking (units)	6		
Virtual stacking (units)	32		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.