



D-Link DGS-1210-52MP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Brand : D-Link

Product code: DGS-1210-52MP

Product name : DGS-1210-52MP

48 x 10/100/1000 Mbps, 4 x SFP, PoE, 104 Gbps, 77.4 Mpps, 48.9 W, 1U, 5.78 kg

D-Link DGS-1210-52MP. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. Full duplex. MAC address table: 16000 entries, Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U



Management features		Power	
Switch type *	Managed	Power consumption (max)	483.1 W
Switch layer	L2	Power over Ethernet (PoE)	
Quality of Service (QoS) support	✓	Power over Ethernet (PoE) *	✓
System event log	✓	Power over Ethernet (PoE) ports quantity	48
Ports & interfaces		Total Power over Ethernet (PoE) budget	370 W
Basic switching RJ-45 Ethernet ports quantity *	48	Operational conditions	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Operating temperature (T-T)	-5 - 50 °C
Gigabit Ethernet (copper) ports quantity	48	Storage temperature (T-T)	-20 - 70 °C
SFP/SFP+ slots quantity	4	Operating relative humidity (H-H)	0 - 95%
SFP module slots quantity	4	Storage relative humidity (H-H)	0 - 95%
Power connector	DC-in jack	Heat dissipation	1648.23 BTU/h
Network		Weight & dimensions	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Width	440 mm
10G support *	✗	Depth	430 mm
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10GBASE-T	Height	44 mm
Port mirroring	✓	Weight	5.78 kg
Full duplex	✓	Packaging data	
Flow control support	✓	Package width	558 mm
Link aggregation	✓	Package depth	568 mm
Broadcast storm control	✓	Package height	149 mm
Auto MDI/MDI-X	✓	Package weight	8.54 kg
Spanning tree protocol	✓	Technical details	
Number of VLANs	4094	Shipping (inner) case height	59.8 cm
Data transmission		Shipping (inner) case width	31.5 cm
Switching capacity *	104 Gbit/s	Shipping (inner) case length	57.4 cm
MAC address table *	16000 entries	Shipping (inner) case net weight	17.1 kg
Packet buffer memory	3 MB	Products per shipping (inner) case	2 pc(s)
Security		Pallet gross weight (air)	245.9 kg
DHCP features	DHCP server, DHCP client	Master (outer) cases per pallet (air)	12 pc(s)
Access Control List (ACL)	✓	Products per pallet (air)	24 pc(s)
		Pallet gross length	110 cm
		Pallet gross width	120 cm
		Pallet height (air)	133.1 cm
		Pallet gross weight (sea)	356.6 kg

Security		Technical details	
IGMP snooping	✓	Master (outer) cases per pallet (sea)	18 pc(s)
MAC address filtering	✓	Products per pallet (sea)	36 pc(s)
SSH/SSL support	✓	Pallet height (sea)	192.9 cm
Design		Shipping (inner) case gross weight	18.4 kg
Rack mounting *	✓	Certificates	
Form factor	1U	Certification	FCC Class A CE Class A ICES-003 VCCI Class A C-Tick BSMI
Product colour	Black	Logistics data	
LED indicators	✓	Harmonized System (HS) code	85176990
Safety	cUL, CE LVD		
Performance			
Flash memory	128 MB		
Mean time between failures (MTBF)	318.616 h		
Power			
AC input voltage	100 - 240 V		
AC input frequency	50 - 60 Hz		



5054629826270



0790069409592



790069409592

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.