D-Link

D-Link DGS-1210-28 network switch Managed L2/L2+ 1U Black

Brand : D-Link **Product code:** DGS-1210-28


Product name: DGS-1210-28






DGS-1210-28 - 24x RJ45, 10/100/1000, IEEE 802.3/u/ab/x, Full Duplex, MAC 16K D-Link DGS-1210-28. Switch type: Managed, Switch layer: L2/L2+. Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Rack mounting, Form factor: 1U

Management features		Weight & dimensions	
Switch type *	Managed	Height	44 mm
Switch layer	L2/L2+	Weight	2.9 kg
Ports & interfaces		Packaging data	
Basic switching RJ-45 Ethernet ports quantity *	24	Package width Package depth	249 mm 493 mm
Network		Package height	72 mm
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Package weight Technical details	3.24 kg
Full duplex	1		20.2
Data transmission		Shipping (inner) case height Shipping (inner) case width Shipping (inner) case length Shipping (inner) case net weight Products per shipping (inner) case Pallet gross weight (air)	28.2 cm 38.1 cm
Supported data transfer rates Switching capacity * MAC address table * Maximum data transfer rate	10/100/1000 56 Gbit/s 16000 entries 2 Gbit/s		51 cm 16.2 kg 5 pc(s) 435.7 kg
Design		Master (outer) cases per pallet (air)	• • •
Rack mounting * Form factor Product colour LED indicators	1U Black	Products per pallet (air) Pallet gross length Pallet gross width Pallet height (air) Pallet gross weight (sea)	120 pc(s) 110 cm 120 cm 130.3 cm 641.3 kg
Performance		Master (outer) cases per pallet (sea)	36 pc(s)
Mean time between failures (MTBF)	236739 h	Products per pallet (sea)	180 pc(s)
Power		Pallet height (sea)	188.7 cm
AC input voltage	100 - 240 V	Shipping (inner) case gross weight	17.1 kg
AC input frequency Power consumption (typical)	50 - 60 Hz 16.81 W	Certificates Certification	FCC Class A, CE Class A, ICES-003, VCCI Class A, C-Tick, BSMI
Operational conditions		Logistics data	7.00. 0.000 7.4 0 7.0.1, 20.1.
Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-5 - 50 °C -20 - 70 °C 0 - 95%	Harmonized System (HS) code	85176990
Weight & dimensions			
Width Depth	440 mm 210 mm		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.