

D-Link DGS-1210-28 verkkokytkin Hallittu L2/L2+ 1U musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-1210-28

Tuotteen nimi : DGS-1210-28



D-Link DGS-1210-28. Kytin tyyppi: Hallittu, Kytinkerros: L2/L2+. Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 56 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Telineasennus, Kotelo: 1U

Management features		Weight & dimensions	
Switch type *	Managed	Height	44 mm
Switch layer	L2/L2+	Weight	2.9 kg
Ports & interfaces		Packaging data	
Basic switching RJ-45 Ethernet ports quantity *	24	Package width	249 mm
		Package depth	493 mm
		Package height	72 mm
		Package weight	3.24 kg
Network		Technical details	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Shipping (inner) case height	28.2 cm
Full duplex	✓	Shipping (inner) case width	38.1 cm
		Shipping (inner) case length	51 cm
		Shipping (inner) case net weight	16.2 kg
		Products per shipping (inner) case	5 pc(s)
		Pallet gross weight (air)	435.7 kg
		Master (outer) cases per pallet (air)	24 pc(s)
		Products per pallet (air)	120 pc(s)
		Pallet gross length	110 cm
		Pallet gross width	120 cm
		Pallet height (air)	130.3 cm
		Pallet gross weight (sea)	641.3 kg
		Master (outer) cases per pallet (sea)	36 pc(s)
		Products per pallet (sea)	180 pc(s)
		Pallet height (sea)	188.7 cm
		Shipping (inner) case gross weight	17.1 kg
Data transmission		Certificates	
Supported data transfer rates	10/100/1000	Certification	FCC Class A, CE Class A, ICES-003, VCCI Class A, C-Tick, BSMI
Switching capacity *	56 Gbit/s		
MAC address table *	16000 entries		
Maximum data transfer rate	2 Gbit/s		
Design		Logistics data	
Rack mounting *	✓	Harmonized System (HS) code	85176990
Form factor	1U		
Product colour	Black		
LED indicators	✓		
Performance			
Mean time between failures (MTBF)	236739 h		
Power			
AC input voltage	100 - 240 V		
AC input frequency	50 - 60 Hz		
Power consumption (typical)	16.81 W		
Operational conditions			
Operating temperature (T-T)	-5 - 50 °C		
Storage temperature (T-T)	-20 - 70 °C		
Operating relative humidity (H-H)	0 - 95%		
Weight & dimensions			
Width	440 mm		
Depth	210 mm		



0790069373008



790069373008




0790069372971



790069372971



0790069372964



790069372964

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.