



D-Link DGS-1210-24P network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : D-Link

Product code: DGS-1210-24P

Product name : DGS-1210-24P

DGS-1210-24P, 802.3af/802.3at/12 ports/85W, 56 Gbps , 41.7 Mpps

D-Link DGS-1210-24P. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. Power over Ethernet (PoE). Rack mounting



Management features		Weight & dimensions	
Switch type *	Managed	Depth	209.9 mm
Switch layer	L2	Height	44 mm
Ports & interfaces		Packaging data	
Basic switching RJ-45 Ethernet ports quantity *	24	Package width	365 mm
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Package depth	521 mm
SFP module slots quantity	4	Package height	92 mm
		Package weight	4.92 kg
Network		Technical details	
Networking standards *	IEEE 802.3af, IEEE 802.3at	Shipping (inner) case height	39.3 cm
Data transmission		Shipping (inner) case width	29.5 cm
Switching capacity *	56 Gbit/s	Shipping (inner) case length	53.9 cm
Throughput	41.7 Mpps	Shipping (inner) case net weight	14.8 kg
Design		Products per shipping (inner) case	3 pc(s)
Rack mounting *	✓	Pallet gross weight (air)	394.9 kg
Product colour	Black	Master (outer) cases per pallet (air)	24 pc(s)
Number of fans	1 fan(s)	Products per pallet (air)	72 pc(s)
Safety	cUL, LVD	Pallet gross length	110 cm
Power		Pallet gross width	120 cm
AC input frequency	50 - 60 Hz	Pallet height (air)	131.4 cm
Power over Ethernet (PoE)		Pallet gross weight (sea)	645.7 kg
Power over Ethernet (PoE) *	✓	Master (outer) cases per pallet (sea)	40 pc(s)
Power over Ethernet (PoE) ports quantity	24	Products per pallet (sea)	120 pc(s)
Operational conditions		Pallet height (sea)	2.1 m
Operating temperature (T-T)	-5 - 50 °C	Shipping (inner) case gross weight	15.6 kg
Storage temperature (T-T)	-20 - 70 °C	Certificates	
Operating relative humidity (H-H)	0 - 95%	Certification	CE Class A
Storage relative humidity (H-H)	0 - 95%	Logistics data	
Weight & dimensions		Harmonized System (HS) code	85176990
Width	441 mm		



0790069391965



790069391965

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.