

## D-Link DGS-1210-16 verkkokytkin Hallittu L2 musta

**Tuotemerkki** : D-Link

**Tuotekoodi**: DGS-1210-16



**Tuotteen nimi** : DGS-1210-16

D-Link DGS-1210-16. Kytkin tyyppi: Hallittu, Kytinkerros: L2. Basic kytkentä RJ-45 Ethernet-porttien määrä: 12. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin. Telineasennus

Management features		Power	
Switch type *	Managed	Power consumption (typical)	17.4 W
Switch layer	L2	<b>Power over Ethernet (PoE)</b>	
Quality of Service (QoS) support	✓	Power over Ethernet (PoE) *	✗
Web-based management	✓	<b>Other features</b>	
System event log	✓	Dimensions (WxDxH)	440 x 210 x 44 mm
MIB support	1213 MIB II, 1493 Bridge MIB, 1907 SNMP v2 MIB, 1215 Trap Convention MIB, 2233 Interface Group MIB, D-Link Private MIB	Connectivity technology	Wired
<b>Ports &amp; interfaces</b>		Packet transfer speed	23.8 Mpps
Basic switching RJ-45 Ethernet ports quantity *	12	Electromagnetic emissions	FCC Class A, CE Class A, IC Class A, VCCI Class A, C-Tick
Combo SFP ports quantity	4	Performance management	Telnet, SNMP, SNMP
SFP/SFP+ slots quantity	4	Connectivity LEDs	✓
Power connector	DC-in jack	Input frequency	50/60 Hz
<b>Network</b>		<b>Operational conditions</b>	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Operating temperature (T-T)	0 - 40 °C
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T	Storage temperature (T-T)	-10 - 70 °C
Port mirroring	✓	Operating relative humidity (H-H)	10 - 95%
Full duplex	✓	Storage relative humidity (H-H)	5 - 95%
Flow control support	✓	Heat dissipation	59.23 BTU/h
Link aggregation	✓	<b>Weight &amp; dimensions</b>	
Broadcast storm control	✓	Weight	2.87 kg
Auto MDI/MDI-X	✓	<b>Packaging data</b>	
Spanning tree protocol	✓	Package width	357 mm
Head-of-line (HOL) blocking	✓	Package depth	331 mm
Number of VLANs	256	Package height	72 mm
<b>Data transmission</b>		Package weight	3 kg
Switching capacity *	32 Gbit/s	<b>Technical details</b>	
MAC address table *	8000 entries	Shipping (inner) case height	38.6 cm
Store-and-forward	✓	Shipping (inner) case width	34.6 cm
Maximum data transfer rate	1 Gbit/s	Shipping (inner) case length	38.2 cm
Packet buffer memory	0.5 MB	Shipping (inner) case net weight	15 kg
<b>Security</b>		Products per shipping (inner) case	5 pc(s)
DHCP features	DHCP client	Pallet gross weight (air)	445.7 kg
Access Control List (ACL)	✓	Master (outer) cases per pallet (air)	27 pc(s)
IGMP snooping	✓	Products per pallet (air)	135 pc(s)
<b>Multicast features</b>		Pallet gross length	110 cm
Multicast support	✓	Pallet gross width	120 cm
		Pallet height (air)	129.3 cm
		Pallet gross weight (sea)	730.4 kg
		Master (outer) cases per pallet (sea)	45 pc(s)
		Products per pallet (sea)	225 pc(s)
		Pallet height (sea)	2.06 m
		Shipping (inner) case gross weight	15.8 kg

Design		Logistics data	
Rack mounting *	✓	Harmonized System (HS) code	85176990
Stackable *	✗		
Product colour	Black		
Safety	cUL, LVD		
Performance			
Noise level	0 dB		
Mean time between failures (MTBF)	799491 h		
Power			
Input voltage	100 - 240 V		



0790069332227



790069332227

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.