



D-Link DGS-1210-08P network switch Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : D-Link

Product code: DGS-1210-08P

Product name : DGS-1210-08P

DGS-1210-08P: 8-Port, Gigabit, PoE, Smart Switch with 2 SFP ports (8 x PoE ports, fanless)
D-Link DGS-1210-08P. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3af. Power over Ethernet (PoE). Rack mounting

Management features		Power	
Switch type *	Managed	Power source *	DC
Switch layer	L2/L3	Input voltage	54 V
Quality of Service (QoS) support	✓	Power consumption (typical)	2.5 W
Web-based management	✓	Power consumption (max)	81.9 W
System event log	✓	Power over Ethernet (PoE)	
MIB support	1213 MIB II, 1493 Bridge MIB, 1907 SNMP v2 MIB, 1215 Trap Convention MIB, 2233 Interface Group MIB, D-Link Private MIB, Power-Ethernet MIB, LLDP MIB, D-Link ZoneDefense MIB1	Power over Ethernet (PoE) *	✓
Ports & interfaces		Power over Ethernet plus (PoE+) ports quantity	8
Basic switching RJ-45 Ethernet ports quantity *	8	Total Power over Ethernet (PoE) budget	65 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Other features	
SFP module slots quantity	2	Packet transfer speed	14.9 Mp/s
Network		Power LED	✓
Networking standards *	IEEE 802.1D, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3af	Operational conditions	
10G support *	✓	Operating temperature (T-T)	-5 - 50 °C
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T	Storage temperature (T-T)	-20 - 70 °C
Port mirroring	✓	Operating relative humidity (H-H)	0 - 95%
Full duplex	✓	Storage relative humidity (H-H)	0 - 95%
Half duplex	✓	Heat dissipation	279.59 BTU/h
Flow control support	✓	Weight & dimensions	
Link aggregation	✓	Width	280 mm
Broadcast storm control	✓	Depth	126 mm
Auto MDI/MDI-X	✓	Height	44 mm
Spanning tree protocol	✓	Weight	950 g
Head-of-line (HOL) blocking	✓	Packaging data	
VLAN support	✓	Package width	288 mm
Data transmission		Package depth	331 mm
Switching capacity *	20 Gbit/s	Package height	72 mm
Forwarding rate	14.88 Mpps	Package weight	2.17 kg
MAC address table *	8000 entries	Technical details	
Store-and-forward	✓	Shipping (inner) case height	31.7 cm
Jumbo frames support	✓	Shipping (inner) case width	34.6 cm
Jumbo frames	10000	Shipping (inner) case length	38.2 cm
Packet buffer memory	4.1 MB	Shipping (inner) case net weight	10.8 kg
Security		Products per shipping (inner) case	5 pc(s)
DHCP features	DHCP server, DHCP client	Pallet gross weight (air)	436.1 kg
Access Control List (ACL)	✓	Master (outer) cases per pallet (air)	36 pc(s)
IGMP snooping	✓	Products per pallet (air)	180 pc(s)
		Pallet gross length	110 cm
		Pallet gross width	120 cm
		Pallet height (air)	140.3 cm
		Pallet gross weight (sea)	644.9 kg

Security		Technical details	
MAC address filtering	✓	Master (outer) cases per pallet (sea)	54 pc(s)
Static port security	✓	Products per pallet (sea)	270 pc(s)
SSH/SSL support	✓	Pallet height (sea)	2.04 m
Multicast features		Shipping (inner) case gross weight	11.6 kg
Multicast support	✓	Certificates	
Protocols		Certification	CE Class A
Management protocols	SNMP, RMON	Logistics data	
Data link protocols	IP	Harmonized System (HS) code	85176990
Design			
Rack mounting *	✓		
Stackable *	✓		
Product colour	Black		
LED indicators	✓		
Cable management	✓		
Safety	cUL, LVD		
Performance			
Mean time between failures (MTBF)	729258 h		



0790069391958



790069391958



5715063468463

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.