D-Link

D-Link DGS-1016D/E verkkokytkin Hallitsematon musta, Metallinen

Tuotemerkki : D-Link Tuotekoodi: DGS-1016D/E

Tuotteen nimi: DGS-1016D/E

D-Link DGS-1016D/E. Kytkin tyyppi: Hallitsematon. Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 32 Gbit/s.

Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Telineasennus





Management features		Operational conditions	
Switch type *	Unmanaged	Operating relative humidity (H-H)	5 - 95%
Quality of Service (QoS) support	✓	Weight & dimensions	
Ports & interfaces Basic switching RJ-45 Ethernet ports quantity *	16	Width Depth Height Weight	281.9 mm 180.3 mm 44.5 mm 1.35 kg
Network	1555 000 4 USES 000 2 USES		1.55 kg
Full duplex	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x X 1000BASE-T, 100BASE-T, 10BASE-T	Packaging data Package width Package depth Package height Package weight	180 mm 328 mm 108 mm 1.71 kg
Flow control support	✓	Technical details	
Auto MDI/MDI-X Data transmission Switching capacity * MAC address table * Store-and-forward Maximum data transfer rate Jumbo frames support Packet buffer memory Design Rack mounting * Stackable * Product colour LED indicators Performance	32 Gbit/s 8000 entries 1 Gbit/s 0.340 MB	Shipping (inner) case height Shipping (inner) case width Shipping (inner) case length Shipping (inner) case net weight Products per shipping (inner) case Pallet gross weight (air) Master (outer) cases per pallet (air) Products per pallet (air) Pallet gross length Pallet gross width Pallet gross weight (sea) Master (outer) cases per pallet (sea) Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	35.9 cm 19.7 cm 57.2 cm 8.54 kg 5 pc(s) 295.7 kg 30 pc(s) 150 pc(s) 110 cm 120 cm 121.2 cm 480.3 kg 50 pc(s) 250 pc(s) 193 cm 9.21 kg
Mean time between failures (MTBF)	828109 h	Certificates	5.21 kg
Power AC input voltage	100 - 240 V	Certification	FCC Class A, CE, ICES-003, VCCI, C-Tick, RoHS
AC input frequency Power consumption (typical)	50 - 60 Hz 11.7 W	Logistics data Harmonized System (HS) code	85176990
Power over Ethernet (PoE)		,	
Power over Ethernet (PoE) *	×		
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		

Operational conditions

Storage temperature (T-T)

-10 - 55 °C









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.