

D-Link DES-108 musta

Tuotemerkki : D-Link

Tuotekoodi: DES-108/E

Tuotteen nimi : DES-108



D-Link DES-108. Basic kytkenä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 1000 entries, Kytkenäkapasiteetti: 1,6 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin

Management features		Other features	
Quality of Service (QoS) support	✓	Dimensions (WxDxH)	162 x 102 x 28 mm
Ports & interfaces		Operational conditions	
Basic switching RJ-45 Ethernet ports quantity *	8	Operating temperature (T-T)	0 - 50 °C
Power connector	DC-in jack	Storage temperature (T-T)	-10 - 70 °C
Network		Operating relative humidity (H-H)	10 - 90%
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Storage relative humidity (H-H)	5 - 90%
10G support *	✗	Packaging data	
Copper ethernet cabling technology	100BASE-TX, 10BASE-T	Package width	208 mm
Full duplex	✓	Package depth	250 mm
Flow control support	✓	Package height	68 mm
Auto MDI/MDI-X	✓	Package weight	610 g
Data transmission		Technical details	
Supported data transfer rates	10/100 Mbps	Shipping (inner) case height	44.3 cm
Switching capacity *	1.6 Gbit/s	Shipping (inner) case width	26 cm
MAC address table *	1000 entries	Shipping (inner) case length	37 cm
Store-and-forward	✓	Shipping (inner) case net weight	6.1 kg
Maximum data transfer rate	0.1 Gbit/s	Products per shipping (inner) case	10 pc(s)
Jumbo frames support	✓	Pallet gross weight (air)	357.5 kg
Packet buffer memory	0.768 MB	Master (outer) cases per pallet (air)	48 pc(s)
Security		Products per pallet (air)	480 pc(s)
MAC address filtering	✓	Pallet gross length	102 cm
Design		Pallet gross width	122 cm
Rack mounting *	✗	Pallet height (air)	2.07 m
Product colour	Black	Pallet gross weight (sea)	357.5 kg
Housing material	Metal	Master (outer) cases per pallet (sea)	48 pc(s)
LED indicators	Link, Power	Products per pallet (sea)	480 pc(s)
Performance		Pallet height (sea)	2.07 m
Mean time between failures (MTBF)	511323 h	Shipping (inner) case gross weight	7 kg
Power		Certificates	
Input current	1 A	Certification	RoHS, FCC Class B, ICES-003 Class B, CE Class B, C-Tick Class B, VCCI Class B, cUL, CB
Input voltage	5 V	Logistics data	
Power consumption (typical)	4.5 W	Harmonized System (HS) code	85176990
Other features			
Data transfer rate	200 Mbit/s		



0790069368202



790069368202

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.