D-Link

D-Link DES-1024D Unmanaged

Brand : D-Link **Product code:** DES-1024D/E

Product name: DES-1024D

24 Port 10/100Mbps Desktop Switch

D-Link DES-1024D Unmanaged:

This desktop switch is designed for small offices and larger workgroups.

All ports auto-sense the network speed of the computers and hubs to run at either 10Mbps or 100Mbps. The ports also auto-negotiate between full and half duplex and support flow control. Expansion is easy through a MDI uplink port. You cascade several switches together through this port to get more ports.

IEEE 802.3x Flow Control allows your servers to directly connect to this switch for fast, reliable data transfer.

D-Link DES-1024D. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 8000 entries. Networking standards: IEEE 802.1D, IEEE 802.3, IEEE 802.3U, IEEE 802.3x

Management features		Packaging data	
Switch type *	Unmanaged	Package width	282 mm
Ports & interfaces		Package depth	376 mm
Basic switching RJ-45 Ethernet ports quantity *	24	Package height Package weight	78 mm 1.9 kg
Network		Technical details	
Networking standards * Full duplex	IEEE 802.1D, IEEE 802.3, IEEE 802.3U, IEEE 802.3x	Shipping (inner) case height Shipping (inner) case width Shipping (inner) case length Shipping (inner) case net weight	31.1 cm 39.2 cm 42 cm
Data transmission	•		9.5 kg
	0000	Products per shipping (inner) case	5 pc(s)
MAC address table * Maximum data transfer rate	8000 entries 0.1 Gbit/s	Pallet gross weight (air)	265.9 kg
	U.1 GDIQS	Master (outer) cases per pallet (air)	24 pc(s)
Design		Products per pallet (air)	120 pc(s)
LED indicators	Power	Pallet gross length	120 cm
Power		Pallet gross width Pallet height (air)	110 cm 137.9 cm
Power consumption (typical)	10 W	Pallet gross weight (sea)	390.3 kg
Power over Ethernet (PoE)		Master (outer) cases per pallet (sea)	•
Power over Ethernet (PoE) *	×	Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	180 pc(s)
Other features			2 m 10.4 kg
Data transfer rate	100 Mbit/s	Logistics data	10.4 Kg
Dimensions (WxDxH) 280 x 180	280 x 180 x 44 mm	-	05176000
Connectivity technology	Wired	Harmonized System (HS) code	85176990
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		
Storage temperature (T-T)	-10 - 70 °C		
Operating relative humidity (H-H)	5 - 90%		
Weight & dimensions			
Weight	2.8 kg		





7900692461116

0790069246111



790069246111

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.