



D-Link DES-1005P Hallitsematon L2 Fast Ethernet (10/100) Power over Ethernet -tuki musta

Tuotemerkki : D-Link

Tuotekoodi: DES-1005P/E

Tuotteen nimi : DES-1005P



D-Link DES-1005P. Kytin tyyppi: Hallitsematon, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Fast Ethernet (10/100), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. Täysin kaksipuolinen. MAC-osoitetaulukko: 2000 entries. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki

Management features		Operational conditions	
Switch type *	Unmanaged	Operating relative humidity (H-H)	10 - 90%
Switch layer	L2	Storage relative humidity (H-H)	5 - 90%
Quality of Service (QoS) support	✓	Weight & dimensions	
Ports & interfaces		Width	140 mm
Basic switching RJ-45 Ethernet ports quantity *	5	Depth	85 mm
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Height	28 mm
Power connector	DC-in jack	Packaging data	
Network		Package width	208 mm
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Package depth	250 mm
10G support *	✗	Package height	68 mm
Full duplex	✓	Package weight	950 g
Auto MDI/MDI-X	✓	Technical details	
Data transmission		Shipping (inner) case height	44.3 cm
MAC address table *	2000 entries	Shipping (inner) case width	26.6 cm
Design		Shipping (inner) case length	37 cm
Rack mounting *	✗	Shipping (inner) case net weight	9.5 kg
Stackable *	✗	Products per shipping (inner) case	10 pc(s)
Product colour	Black	Pallet gross weight (air)	514.6 kg
LED indicators	✓	Master (outer) cases per pallet (air)	48 pc(s)
Performance		Products per pallet (air)	480 pc(s)
Mean time between failures (MTBF)	324616 h	Pallet gross length	110 cm
Power over Ethernet (PoE)		Pallet gross width	120 cm
Power over Ethernet (PoE) *	✓	Pallet height (air)	196.7 cm
Power over Ethernet (PoE) ports quantity	1	Pallet gross weight (sea)	514.6 kg
Power over Ethernet (PoE) power per port	15.4 W	Master (outer) cases per pallet (sea)	48 pc(s)
Other features		Products per pallet (sea)	480 pc(s)
Power LED	✓	Pallet height (sea)	196.7 cm
Operational conditions		Shipping (inner) case gross weight	10.2 kg
Operating temperature (T-T)	0 - 40 °C	Certificates	
Storage temperature (T-T)	-40 - 70 °C	Certification	RoHS, FCC, CE, cUL, ICES-003 B
		Logistics data	
		Harmonized System (HS) code	85176990



0790069370908



790069370908

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.