



D-Link DEM-432XT network transceiver module Fiber optic 10000 Mbit/s SFP+ 1310 nm

Brand : D-Link

Product code: DEM-432XT

Product name : DEM-432XT




D-Link DEM-432XT. SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Maximum voltage: 3.3 V, Maximum current: 300 A. Compliance certificates: RoHS, Safety: UL, TUV, CDRH, Certification: CE, FCC, VCCI. Width: 14.8 mm, Depth: 11.8 mm, Height: 56.5 mm. Package width: 74 mm, Package depth: 131 mm, Package height: 49 mm

Performance		Weight & dimensions	
SFP transceiver type *	Fiber optic	Depth	11.8 mm
Maximum data transfer rate *	10000 Mbit/s	Height	56.5 mm
Interface type *	SFP+	Weight	19.5 g
Single-mode fiber (SMF) supported	✓	Packaging data	
Fiber optic connector	LC	Package width	74 mm
Fiber cable diameters supported (core/cladding)	9/125 µm	Package depth	131 mm
Maximum transfer distance	10000 m	Package height	49 mm
Wavelength	1310 nm	Package weight	64 g
Tx power (min)	-8.5 dBmW	Logistics data	
Tx power (max)	0.5 dBmW	Shipping (inner) case length	36 cm
Rx power (min)	-12.6 dBmW	Shipping (inner) case width	26 cm
Rx power (max)	0.5 dBmW	Shipping (inner) case height	31 cm
Networking standards	IEEE 802.3ae	Shipping (inner) case net weight	3.2 kg
Power		Products per shipping (inner) case	50 pc(s)
Maximum voltage	3.3 V	Pallet gross weight (air)	272 kg
Maximum current	300 A	Master (outer) cases per pallet (air)	60 pc(s)
Certificates		Products per pallet (air)	3000 pc(s)
Compliance certificates	RoHS	Pallet gross length	102 cm
Safety	UL, TUV, CDRH	Pallet gross width	122 cm
Certification	CE, FCC, VCCI	Pallet height (air)	199 cm
Operational conditions		Pallet gross weight (sea)	272 kg
Operating temperature (T-T)	0 - 70 °C	Master (outer) cases per pallet (sea)	60 pc(s)
Storage temperature (T-T)	-40 - 85 °C	Products per pallet (sea)	3000 pc(s)
Operating relative humidity (H-H)	5 - 85%	Pallet height (sea)	199 cm
Storage relative humidity (H-H)	5 - 95%	Shipping (inner) case gross weight	4.2 kg
Weight & dimensions		Harmonized System (HS) code	85369010
Width	14.8 mm		



0790069353208




790069353208



7900693532082



0790069353215



790069353215



0790069353192



790069353192

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.