D-Link

D-Link DEM-432XT lähetin-vastaanotinmoduuli Valokuitu 10000 Mbit/s SFP+ 1310 nm

Tuotemerkki : D-Link Tuotekoodi: DEM-432XT


Tuotteen nimi: DEM-432XT

D-Link DEM-432XT. SFP-vastaanottimen tyyppi: Valokuitu, Tiedonsiirron enimmäisnopeus: 10000 Mbit/s, PCI-väylä: SFP+. Maksimijännite: 3,3 V, Enimmäisvirta: 300 A. Vaatimustenmukaisuustodistukset: RoHS, Turvallisuus: UL, TUV, CDRH, Sertifiointi: CE, FCC, VCCI. Tuotteen leveys: 14,8 mm, Tuotteen syvyys: 11,8 mm, Tuotteen korkeus: 56,5 mm. Pakkauksen leveys: 74 mm, Pakkauksen syvyys: 131 mm,

Pakkauksen korkeus: 49 mm




Performance		Weight & dimensions	
SFP transceiver type * Maximum data transfer rate *	Fiber optic 10000 Mbit/s	Depth Height	11.8 mm 56.5 mm
Interface type *	SFP+	Weight	19.5 g
Single-mode fiber (SMF) supported	✓	Packaging data	
Fiber optic connector	LC	Package width	74 mm
Fiber cable diameters supported (core/cladding)	9/125 μm	Package depth Package height	131 mm 49 mm
Maximum transfer distance	10000 m	Package weight	64 q
Wavelength	1310 nm	3 3	04 g
Tx power (min)	-8.5 dBmW	Logistics data	
Tx power (max)	0.5 dBmW	Shipping (inner) case length	36 cm
Rx power (min)	-12.6 dBmW	Shipping (inner) case width	26 cm
Rx power (max)	0.5 dBmW	Shipping (inner) case height	31 cm
Networking standards	IEEE 802.3ae	Shipping (inner) case net weight	3.2 kg
Power		Products per shipping (inner) case	50 pc(s)
Maximum voltage	3.3 V	Pallet gross weight (air)	272 kg
Maximum current	300 A	Master (outer) cases per pallet (air)	60 pc(s)
Certificates		Products per pallet (air) Pallet gross length	3000 pc(s) 102 cm
Compliance certificates	RoHS	Pallet gross width	122 cm
Safety	UL, TUV, CDRH	Pallet height (air)	199 cm
Certification	CE, FCC, VCCI	Pallet gross weight (sea)	272 kg
Operational conditions		Master (outer) cases per pallet (sea)	• • •
Operating temperature (T-T)	0 - 70 °C	Products per pallet (sea)	3000 pc(s)
Storage temperature (T-T)	-40 - 85 °C	Pallet height (sea)	199 cm
Operating relative humidity (H-H)	5 - 85%	Shipping (inner) case gross weight	4.2 kg
Storage relative humidity (H-H)	5 - 95%	Harmonized System (HS) code	85369010
Weight & dimensions			
Width	14.8 mm		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.