## ATEN CS1924M-AT-G KVM-kytkin musta

Tuotemerkki : ATEN

Tuotekoodi: CS1924M-AT-G

Tuotteen nimi : CS1924M-AT-G


ATEN CS1924M-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: HDMI. HDtyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli, Muovi. Voimanlähde: DC, Tulojännite: 5 V, Virrankulutus: 4,89 W. Tuotteen leveys: 270 mm, Tuotteen syvyys: 88 mm, Tuotteen korkeus: 55,5 mm



## Ports & interfaces

| Ports & interfaces                                     |   | Power  |                        |
|--|---|--|------------------------|
| Number of computers controlled *                       | 4   | Power consumption (typical)                                    | 4.89 W                 |
| Keyboard port type *                                   | USB   | System requirements  |                        |
| Mouse port type *<br>Video port type *                 | USB<br>HDMI   | Windows operating systems                                      | /                      |
| DisplayPorts quantity                                  | 4   | supported  |                        |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-B                       |   | Operational conditions   |                        |
| ports quantity   |   | Operating temperature (T-T)                                    | 0 - 50 °C              |
| Console ports *  | 3.5mm headphone, 3.5mm mic,<br>DisplayPort, HDMI, USB A | Storage temperature (T-T)<br>Operating relative humidity (H-H) | -20 - 60 °C<br>0 - 80% |
| Console USB ports quantity                             | 2   | Storage relative humidity (H-H)                                | 0 - 80%                |
| USB hub  | ✓   | Weight & dimensions  |                        |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A<br>hub ports quantity | 2   | Width  | 270 mm                 |
| USB connector type                                     | USB Type-A, USB Type-B                                  | Depth  | 88 mm                  |
| Audio connections                                      | 1   | Height   | 55.5 mm                |
| Headphone outputs                                      | 6   | Weight   | 2.01 kg                |
| Number of microphone inputs                            | 6   | Packaging data   |                        |
| DC-in jack   | <i>✓</i>  | Package width  | 98 mm                  |
| Performance  |   | Package depth  | 325 mm                 |
| HD type *  | 4K Ultra HD   | Package height Package weight                                  | 210 mm<br>2.56 kg      |
| Maximum resolution *                                   | 4096 x 2160 pixels                                      |  | 2.30 kg                |
| Video bandwidth  | 60 Hz   | Packaging content  |                        |
| Scan interval  | 1,5,99 s  | Quick installation guide                                       | ✓                      |
| Design   |   | Manual   | ✓                      |
| Product colour *                                       | Black<br>Matal Plastic                                  | Logistics data   |                        |
| Housing material<br>LED indicators                     | Metal, Plastic  | Master (outer) case net weight                                 | 10.1 kg                |
| Push button  | v<br>V  | Harmonized System (HS) code<br>Master (outer) case width       | 85176200<br>342 mm     |
| Hot keys   | ·   | Master (outer) case length                                     | 512 mm                 |
|  | •   | Master (outer) case height                                     | 232 mm                 |
| Display  |   | Master (outer) case gross weight 13.7 kg                       |                        |
| Built-in display *                                     | ×   | Products per master (outer) case                               | 5 pc(s)                |
| Power  |   |  |                        |
| Power source   | DC  |  |                        |

| Power         |     |
|---------------|-----|
| Input voltage | 5 V |



4719264645839

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.