



ATEN VE1812-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin musta

Tuotemerkki : ATEN

Tuotekoodi: VE1812-AT-G

Tuotteen nimi : VE1812-AT-G

ATEN VE1812-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6, Cat6a. Yhteysteknologia: Langallinen. Käyttöjännite (lähetin): 5 V, Käyttöjännite (vastaanotin): 5 V, Tehonkulutus (lähetin) (max): 3,2 W. Paino: 1,3 kg, Vastaanottimen mitat (L x S x K): 123 x 140,4 x 30 mm, Vastaanottimen paino: 450 g. Lukumäärä per pakkaus: 1 kpl, Pakkauksen leveys: 100 mm, Pakkauksen syvyys: 283 mm



Features		Power	
Type *	AV transmitter & receiver	Operating voltage (receiver)	5 V
Maximum resolution *	4096 x 2160 pixels	Power consumption (transmitter) (max)	3.2 W
Cable types supported	Cat5e, Cat6, Cat6a	Power consumption (receiver) (max)	5.33 W
Maximum transfer distance	150 m	External power adapter	✓
LED indicators	✓	Operational conditions	
Supported video modes	1080p	Operating temperature (T-T)	0 - 40 °C
Supported graphics resolutions	3840 x 2160, 4096 x 2160	Storage temperature (T-T)	-20 - 60 °C
Bandwidth	10.2 Gbit/s	Operating relative humidity (H-H)	0 - 80%
Bandwidth	340 MHz	Weight & dimensions	
HDCP	✓	Weight	1.3 kg
Material	Metal	Receiver dimensions (WxDxH)	123 x 140.4 x 30 mm
3D	✓	Receiver weight	450 g
Firmware upgradeable	✓	Transmitter dimensions (WxDxH)	123 x 140.4 x 30 mm
Consumer Electronics Control (CEC) support	✓	Transmitter weight	470 g
Impedance	100 Ω	Packaging data	
HDCP version	2.2	Quantity per pack	1 pc(s)
Product colour	Black	Package width	100 mm
Ports & interfaces		Package depth	283 mm
Connectivity technology *	Wired	Package height	173 mm
Ethernet LAN	✓	Package weight	1.4 kg
RJ-45 input ports	1	Packaging content	
RJ-45 output ports	1	AC adapter included	✓
HDBaseT port	✓	Quick start guide	✓
HDMI in	1	Technical details	
Number of HDMI outputs	1	Compliance certificates	RoHS
RS-232 input ports	1	Logistics data	
RS-232 output ports	1	Master (outer) case width	292 mm
Video in	1	Master (outer) case length	517 mm
Video out	1	Master (outer) case height	194 mm
3.5 mm (1/8-inch) in	✓	Master (outer) case gross weight	6.98 kg
3.5 mm (1/8-inch) out	✓	Master (outer) case net weight	6.5 kg
Remote (IR) input	1		
Remote (IR) output	1		

Ports & interfaces

DC-in jack

**Logistics data**

Products per master (outer) case 5 pc(s)

Power

Operating voltage (transmitter) 5 V



4719264645792

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date