



ATEN VE157-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin Valkoinen

Tuotemerkki : ATEN

Tuotekoodi: VE157-AT-G

Tuotteen nimi : VE157-AT-G



ATEN VE157-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6. Yhteysteknologia: Langallinen. Käyttöjännite (lähetin): 9 V, Käyttöjännite (vastaanotin): 9 V, Tehonkulutus (lähetin) (max): 1,65 W. Paino: 445 g, Vastaanottimen mitat (L x S x K): 44,4 x 68,6 x 42,8 mm, Vastaanottimen paino: 180 g. Lukumäärä per pakkaus: 2 kpl, Pakkauksen leveys: 59 mm, Pakkauksen syvyys: 239 mm



Features		Power	
Type *	AV transmitter & receiver	Power consumption (transmitter) (max)	1.65 W
Maximum resolution *	1920 x 1200 pixels	Power consumption (receiver) (max)	0.95 W
Cable types supported	Cat5e, Cat6	External power adapter	✓
Maximum transfer distance	150 m	Operational conditions	
Audio system	stereo	Operating temperature (T-T)	0 - 50 °C
Electrostatic Discharge (ESD) protection	✓	Storage temperature (T-T)	-20 - 60 °C
Electrostatic Discharge (ESD) protection	15 kV	Operating relative humidity (H-H)	0 - 80%
LED indicators	✓	Weight & dimensions	
Supported graphics resolutions	1280 x 1024 (SXGA), 1920 x 1200 (WUXGA)	Weight	445 g
Bandwidth	300 MHz	Receiver dimensions (WxDxH)	44.4 x 68.6 x 42.8 mm
Resolution	1920 x 1200 pixels	Receiver weight	180 g
Material	Metal	Transmitter dimensions (WxDxH)	44.4 x 68.6 x 42.8 mm
Plug and Play	✓	Transmitter weight	180 g
Impedance	100 Ω	Packaging data	
Product colour	White	Quantity per pack	2 pc(s)
Ports & interfaces		Package width	59 mm
Connectivity technology *	Wired	Package depth	239 mm
Ethernet LAN	✓	Package height	160 mm
RJ-45 input ports	1	Package weight	606 g
RJ-45 output ports	1	Packaging content	
VGA (D-Sub) input ports	1	AC adapter included	✓
VGA (D-Sub) output ports	1	Quick start guide	✓
Video in	1	Logistics data	
Video out	1	Master (outer) case width	250 mm
VGA (D-Sub) ports quantity	2	Master (outer) case length	325 mm
Audio input	1	Master (outer) case height	175 mm
Audio output	1	Master (outer) case gross weight	3.45 kg
Power		Master (outer) case net weight	2.23 kg
Operating voltage (transmitter)	9 V	Products per master (outer) case	5 pc(s)
Operating voltage (receiver)	9 V		



4719264645693

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-APR-2025. Prints or copies of Information are only valid on the printed Publication date