## D-Link

## D-Link DWA-172 verkkokortti WLAN 433 Mbit/s

**Tuotemerkki**: D-Link **Tuotekoodi**: DWA-172

Tuotteen nimi: DWA-172

D-Link DWA-172. Yhteysteknologia: Langaton, Isäntäkoneen käyttöliittymä: USB, Käyttöliittymä: WLAN. Tiedonsiirron enimmäisnopeus: 433 Mbit/s, Wi-Fi-standardi: Wi-Fi 5 (802.11ac), Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz)

Ports & interfaces		Weight & dimensions	
Connectivity technology * Host interface * Interface * USB ports quantity	Wireless USB WLAN 1	Width Depth Height Weight	15.7 mm 15 mm 193 mm 23.2 g
Network		Packaging data	
Maximum data transfer rate *  Networking standards *  Ethernet LAN	433 Mbit/s IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Quantity Package width Package depth Package height Package weight	1 137 mm 208 mm 36 mm 60 g
Wi-Fi	✓	Logistics data	-
Wi-Fi band Frequency range Top Wi-Fi standard Wi-Fi standards WLAN data transfer rates supported Security algorithms  Design Internal * Antenna LED indicators	Dual-band (2.4 GHz / 5 GHz) 2.4 - 5 GHz Wi-Fi 5 (802.11ac) 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n) 1,2,5.5,11,12,24,36,48,54,150,433 Mbit/s WPA, WPA2, WPS  *  *CC Class B IC CE C-Tick Wi-Fi	Harmonized System (HS) code Shipping (inner) case net weight Shipping (inner) case length Shipping (inner) case height Shipping (inner) case width Products per shipping (inner) case Pallet gross weight (air) Master (outer) cases per pallet (air) Products per pallet (air) Pallet height (air) Pallet gross weight (sea) Master (outer) cases per pallet (sea) Products per pallet (sea)	85176990 6.3 kg 45.7 cm 32 cm 44.3 cm 40 pc(s) 191.2 kg 24 pc(s) 960 pc(s) 2.1 m 191.2 kg 24 pc(s) 960 pc(s)
Certification	Certified Wi-Fi Protected Setup	Pallet height (sea)	2.1 m
Power		Shipping (inner) case gross weight	7.3 kg
Output voltage	5 V	Pallet gross width	110 cm 120 cm
System requirements		Pallet gross length	120 (11)
Windows operating systems supported	✓	Other features Gain	3 dBi
Operational conditions			
Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -20 - 75 °C 10 - 90% 5 - 95%		





790069405495

0790069405495



7900694054958

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.