

APC MGE Galaxy 3500 20kVA 400V uninterruptible power supply (UPS) 16000 W

Brand : APC Product code: G35T20KH3B4S

Product name: MGE Galaxy 3500 20kVA 400V

MGE Galaxy 3500 20kVA 400V with 3 Battery Modules Expandable to 4, Start-up 5X8 APC MGE Galaxy 3500 20kVA 400V. Output power capacity: 20 kVA, Output power: 16000 W, Input frequency: 40/70 Hz. Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 5 h. Product colour: Black, Certification: CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO.... Weight: 535 kg, Package weight: 565 kg. Battery type: VRLA, Output connections: 1×4 -wire (3PH + G) 1×5 -wire (3PH + N + G) 1×5 -wire (3PH + N + G)



Features		Operational conditions	
Output power capacity * Output power * Input frequency * Maximum current	20 kVA 16000 W 40/70 Hz 27 A	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 95% 0 - 95% 0 - 999.9 m 0 - 15000 m
Emergency Power Off (EPO)	/	Weight & dimensions	
Noise level	51.3 dB	Weight	535 kg
Battery		Package weight	565 kg
Battery technology	Sealed Lead Acid (VRLA)	Logistics data	
Battery recharge time	5 h 2	Harmonized System (HS) code	85078000
Replacement battery cartridge	2	Other features	
Design		Battery type	VRLA
Product colour *	Black CE,EN 50091-2,EN/IEC	Output connections	1×4 -wire (3PH + G) 1×5 -wire (3PH + N + G) 1×5 -rew Terminals
Certification	62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO 9001,VFI-SS-111	Input connection type	5-wire (3PH + N + G)
		Dimensions (WxDxH)	523 x 838 x 1491 mm
Operational conditions		Nominal output voltage	400 V
Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -15 - 45 °C	Output voltage note Package dimensions (WxDxH)	+/-1%, +/- 5% 650 x 1062 x 1643 mm

