

## APC MGE Galaxy 3500 20kVA 400V UPS-virtalähde 16000 W

Tuotemerkki : APC Tuotekoodi: G35T20KH3B4S

Tuotteen nimi: MGE Galaxy 3500 20kVA 400V

APC MGE Galaxy 3500 20kVA 400V. Kokonaislähtöteho (VA): 20 kVA, Lähtöteho: 16000 W, Syötteen taajuus: 40/70 Hz. Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 5 h. Tuotteen väri: musta, Sertifiointi: CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO.... Paino: 535 kg, Pakkauksen paino: 565 kg. Akkutyyppi: VRLA, Lähtöliittimet:  $1 \times 4$ -wire (3PH + G)  $1 \times 5$ -wire (3PH + N + G)  $1 \times 5$ -wire (3PH + N + G)



Features		Operational conditions	
• •	16000 W 40/70 Hz	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 95% 0 - 95% 0 - 999.9 m 0 - 15000 m
Emergency Power Off (EPO)	✓	Weight & dimensions	
Noise level	51.3 dB	Weight	535 kg
Battery		Package weight	565 kg
Battery technology	Sealed Lead Acid (VRLA)	Logistics data	
Battery recharge time	5 h	Harmonized System (HS) code	85078000
Replacement battery cartridge	2	Other features	
Design		Battery type	VRLA
Product colour *	Black CE,EN 50091-2,EN/IEC	Output connections	1 x 4-wire (3PH + G) 1 x 5-wire (3PH + N + G) 1 x Screw Terminals
Certification	62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO 9001,VFI-SS-111	Input connection type	5-wire (3PH + N + G)
		Dimensions (WxDxH)	523 x 838 x 1491 mm
Operational conditions		Nominal output voltage	400 V
Operating temperature (T-T)	0 - 40 °C	Output voltage note	+/-1%, +/- 5%
Storage temperature (T-T)	-15 - 45 °C	Package dimensions (WxDxH)	650 x 1062 x 1643 mm

