

APC MGE Galaxy 3500 20kVA 400V 3:1 uninterruptible power supply (UPS) 16000 W

Brand : APC Product code: G35T20K3I2B4S

Product name: MGE Galaxy 3500 20kVA 400V 3:1

MGE Galaxy 3500 20kVA 400V 3:1 with 2 Battery Modules Expandable to 4, Start-up 5X8 APC MGE Galaxy 3500 20kVA 400V 3:1. Output power capacity: 20 kVA, Output power: 16000 W, Input frequency: 40/70 Hz. Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 5 h. Product colour: Black, Certification: CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO.... Weight: 472 kg, Package weight: 505 kg. Battery type: VRLA, Output connections: 1×4 -wire (3PH + G) 1×5 -wire (3PH + N + G) 1×5 -wire (3PH + N + G)



Features		Operational conditions	
Output power capacity * Output power * Input frequency * Maximum current Emergency Power Off (EPO)	20 kVA 16000 W 40/70 Hz 27 A ✓	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	-15 - 45 °C 0 - 95% 0 - 95% 0 - 999.9 m 0 - 15000 m
Noise level	51.3 dB	Weight & dimensions	
Battery Battery technology Battery recharge time Replacement battery cartridge	Sealed Lead Acid (VRLA) 5 h 2	Weight Package weight Other features Battery type	472 kg 505 kg VRLA
Design Product colour * Certification	Black CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO 9001,VFI-SS-111	Output connections Input connection type Dimensions (WxDxH) Output voltage note Package dimensions (WxDxH)	1 x 4-wire (3PH + G) 1 x 5-wire (3PH + N + G) 1 x Screw Terminals 5-wire (3PH + N + G) 523 x 838 x 1491 mm +/-1%, +/- 5% 650 x 1062 x 1643 mm
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		

