

Chieftec GDP-650C power supply unit 650 W 20+4 pin ATX PS/2 Black

Brand : Chieftec

Product code: GDP-650C

Product name : GDP-650C



650W, 20+4PIN, 8PIN EPS (4+4), SATA x 6, Molex x 3, Floppy, 8PIN PCIe (6+2) x 2

Chieftec GDP-650C power supply unit 650 W 20+4 pin ATX PS/2 Black:

Efficiency at low cost, that's the reason, why the new A-90 series from CHIEFTEC has been invented. The three high performance PSU's cover with their nominal power output of 550 watts - 750 watts all kinds of usage possibilities. With a fixed output voltage of 230 V, this power supply series is especially made for cost-aware computer consumers. The PSU's have an efficiency of >90% and thus meet the 80plus gold requirements.

Chieftec GDP-650C. Total power: 650 W, AC input voltage: 200 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Semi-Modular. Purpose: PC, Power supply unit (PSU) form factor: PS/2, Mean time between failures (MTBF): 100000 h. Product colour: Black, Fan diameter: 14 cm. Width: 150 mm, Depth: 160 mm, Height: 87 mm

Power		Ports & interfaces	
Total power *	650 W	CPU power connector (4+4 pin)	✓
AC input voltage *	200 - 240 V	Floppy drive power connector	1
AC input frequency	47 - 63 Hz	Cabling type	Semi-Modular
Input current	5 A	Performance	
Power Factor Correction (PFC) type	Active	Purpose *	PC
Combined power (+3.3V)	120 W	Power supply unit (PSU) form factor *	PS/2
Combined power (+5V)	120 W	ATX version	2.3
Max output current (+3.3V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V1)	53 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Fan diameter	14 cm
Max output current (+5Vsb)	2.5 A	Weight & dimensions	
Power protection features	Over current, Over voltage, Overheating, Overload, Short circuit, Under voltage	Width	150 mm
		Depth	160 mm
		Height	87 mm
Ports & interfaces		Technical details	
Motherboard power connector *	20+4 pin ATX	Compliance certificates	RoHS
Number of SATA power connectors	6	Logistics data	
Peripheral (Molex) power connectors (4-pin) *	3	Harmonized System (HS) code	84733020
PCI Express power connectors (6+2 pin)	2		



4710713230835

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-NOV-2024. Prints or copies of Information are only valid on the printed Publication date