Epson FX-2190II dot matrix printer 240 x 144 DPI 738 cps

Brand: Epson Product code: C11CF38401

Product name: FX-2190II

- Market-leading print speeds:Complete your high-volume print runs even faster
- Very low TCO: Cheap, long-lasting consumables and low power use
- Even better reliability: Improved by 25 percent to 25,000 power-on hours
- Smaller footprint: Allows for easy placement within a business environment
- Energy Star compliant: To ensure the best possible energy efficiency

Impact Dot Matrix, 9pins, 136colums, 18 Needles (2 \times 9), 738chars/s, 240 \times 144DPI, USB, Ethernet, 54W, 55dB, 128kB, ESC/P, IBM PPDS


Epson FX-2190II. Maximum print speed: 738 cps, Maximum resolution: 240 x 144 DPI, Maximum print speed (draft): 463 cps. Maximum print size: A3 (297 x 420 mm), Paper tray media types: Envelopes, Continuous paper thickness range: 0.46 - 0.46 mm. Product colour: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Parallel, USB. Print head: 9-pin, Print direction: Bidirectional, Print head life: 400 million characters





Printing		Power	
Maximum resolution * Maximum printing width (columns)	240 x 144 DPI * 136	Power consumption (economy mode)	0.5 W
Colour *	X	Operational conditions	
Maximum print speed * Maximum print speed (draft) Maximum print speed (NLQ) Character pitch	738 cps 463 cps 115 cps 10,12,15 cpi	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 35 °C -30 - 60 °C 10 - 80% 30 - 60%
Maximum number of copies	6 copies	Weight & dimensions	
Built-in barcodes Bitmap fonts	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Industrial 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E Draft, OCR-B, Roman, Sans Serif	Width Depth Height	612 mm 375 mm 177 mm
·	PCAPTEC, PC437, PC720, PC850,	Weight	8.37 kg
Character sets Number of characters	PC858, ISO 8859-15, Roman 8, Italic 42		,
Paper handling		Quantity per pack Package width	1 pc(s) 455 mm
Maximum print size Paper tray media types Continuous paper thickness range Label thickness range Multi-part paper thickness range	A3 (297 x 420 mm) Envelopes 0.46 - 0.46 mm 0.46 - 0.46 mm 0.12 - 0.46 mm	Package depth Package height Package weight Other features	735 mm 300 mm 12.1 kg
Single sheet thickness range Features	0.06 - 0.14 mm	Standard media sizes	Sheet Paper (single- and multi- layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard
Product colour * Buffer size * Sound pressure level (printing) * Page description languages *	Black 128 KB 55 dB ESC P, PPDS	Connectivity technology Print technology Box contents	Cardboard Wired Dot matrix AC cable, Driver and utilities (CD), Ribbon, User quide
Country of origin	Indonesia	Needles	18 Needles (2 x 9)
Ports & interfaces		Technical details	
Standard interfaces *	Parallel, USB	Sustainability certificates	ENERGY STAR
Endurance		Logistics data	
Print head *	9-pin		14 nc/s)
	·	Products per pallet	14 pc(s)

Endurance		Logistics data	
Print direction	Bidirectional	Pallet gross weight	0 g
Print head life	400 million characters	Pallet gross length	120 cm
Ribbon life (black, draft)	12 million characters	Pallet gross width	80 cm
Print yield	12 characters	Pallet gross height	2.25 m
Mean time between failures (MTBF)	25000 h	Products per pallet layer	2 pc(s)
Power		Products per pallet layer (UK)	3 pc(s)
Power consumption (typical)	54 W	Products per pallet (UK)	21 pc(s)
Power consumption (typical)	8 W	Pallet weight (UK)	0 g
1 , , , , , , , , , , , , , , , , , , ,		Pallet length (UK)	120 cm
AC input voltage	198-264 V	Pallet width (UK)	100 cm
		Pallet height (UK)	2.25 m
		Harmonized System (HS) code	84433210



8715946645636

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.