## D-Link GO-SW-8E/E network switch Unmanaged Fast Ethernet (10/100) White

Brand : D-Link

Product code: GO-SW-8E/E


D-link . . . . . . . . . .

Product name : GO-SW-8E/E

## 8x 10BASE-T, 1.6Gbps, 2K MAC, 141.5 x 78.5 x 23.8 mm

D-Link GO-SW-8E/E. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 2000 entries. Networking standards: IEEE 802.3, IEEE 802.3az, IEEE 802.3x. Power connector: DC-in jack

Management features		Weight & dimensions	
Switch type *	Unmanaged	Width	141.5 mm
Ports & interfaces		Depth	78.5 mm
Basic switching RJ-45 Ethernet ports	S o	Height	23.8 mm
quantity *	0	Packaging data	
Basic switching RJ-45 Ethernet ports type *	<sup>s</sup> Fast Ethernet (10/100)	Package width	104 mm
Power connector	DC-in jack	Package depth	158 mm
Network		Package height Package weight	94 mm 282.8 g
Networking standards *	IEEE 802.3, IEEE 802.3az, IEEE	Technical details	
-	802.3x	Shipping (inner) case height	35 cm
10G support *	×	Shipping (inner) case width	21.1 cm
Full duplex	✓	Shipping (inner) case length	54.3 cm
Auto MDI/MDI-X	<ul> <li>Image: A second s</li></ul>	Shipping (inner) case net weight	3.82 kg
Data transmission		Products per shipping (inner) case	20 pc(s)
MAC address table *	2000 entries	Pallet gross weight (air)	333.7 kg
Store-and-forward	1	Master (outer) cases per pallet (air)	50 pc(s)
Jumbo frames support	1	Products per pallet (air)	1000 pc(s)
Design		Pallet gross length Pallet gross width	110 cm 120 cm
Rack mounting *	×	Pallet height (air)	188.5 cm
Stackable *		Pallet gross weight (sea)	333.7 kg
Product colour	× White	Master (outer) cases per pallet (sea)	5
LED indicators		Products per pallet (sea)	1000 pc(s)
	<ul> <li>Image: A start of the start of</li></ul>	Pallet height (sea)	188.5 cm
Power over Ethernet (PoE)		Shipping (inner) case gross weight	6.28 kg
Power over Ethernet (PoE) *	×	Logistics data	
Other features		Harmonized System (HS) code	85176990
Power LED	✓		
Operational conditions			
Operating temperature (T-T)	0 - 40 °C		
Storage temperature (T-T)	-10 - 70 °C		
Operating relative humidity (H-H)	10 - 90%		
Storage relative humidity (H-H)	5 - 90%		





7900693882866

0790069388286



790069388286

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.