
## D-Link

## D-Link GO-SW-24G Hallitsematon L2 Gigabit Ethernet (10/100/1000) 1U musta

Tuotemerkki : D-Link Tuotekoodi: GO-SW-24G/E

Tuotteen nimi: GO-SW-24G







Management features		Power	
Switch type *	Unmanaged	Power consumption (max)	15.4 W
Switch layer	L2	Power over Ethernet (PoE)	
Quality of Service (QoS) support	<b>✓</b>	Power over Ethernet (PoE) *	×
Ports & interfaces		Operational conditions	
Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports type * Gigabit Ethernet (copper) ports quantity		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Heat dissipation	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 95% 52.54 BTU/h
Network		Weight & dimensions	
Networking standards *  10G support *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x  X 1000BASE-T, 100BASE-TX, 10BASE-	Width Depth Height Weight	280 mm 180 mm 44 mm 1.35 kg
Copper ethernet cabling technology	T	Packaging data	
Full duplex	✓	Package width	245 mm
Half duplex	✓	Package depth	438 mm
Flow control support	✓	Package height	77 mm
Auto MDI/MDI-X	✓	Package weight	2.3 kg
Ethernet LAN data rates	10,100,1000 Mbit/s	Technical details	
Auto-negotiation	✓	Shipping (inner) case height	27 cm
Data transmission		Shipping (inner) case width	41.3 cm
Switching capacity * Forwarding rate MAC address table * Store-and-forward Number of queues Jumbo frames support Jumbo frames Packet buffer memory	48 Gbit/s 35.71 Mpps 8000 entries   8  9216 0.512 MB	Shipping (inner) case length Shipping (inner) case net weight Products per shipping (inner) case Pallet gross weight (air) Master (outer) cases per pallet (air) Products per pallet (air) Pallet gross length Pallet gross width Pallet height (air)	46.3 cm 11.5 kg 5 pc(s) 373.6 kg 28 pc(s) 140 pc(s) 110 cm 120 cm 2.02 m
Design		Pallet gross weight (sea)	373.6 kg
Rack mounting * Form factor Product colour Housing material	1U Black Metal	Master (outer) cases per pallet (sea) Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	140 pc(s) 2.02 m

Design		Certificates	
LED indicators Number of fans	<b>✓</b> 0 fan(s)	Certification	CE Class A, FCC Class A, VCCI Class A, BSMI, CCC UL, CB, LVD, BSMI, CCC
Performance		Logistics data	
Mean time between failures (MTBF)	302287 h	Harmonized System (HS) code	85176990
Power			









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.