

D-Link DGS-3630-52TC Hallittu L3 Gigabit Ethernet (10/100/1000) 1U musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-3630-52TC/SI

Tuotteen nimi : DGS-3630-52TC

D-Link DGS-3630-52TC. Kytkein tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 44, USB 2.0 - porttien määrä: 1, Console-portti: RJ-45/Mini-USB. Täysin kaksipuolinen. MAC-osoitetaulukko: 68000 entries, Kytkentäkapasiteetti: 176 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qbb, IEEE 802.1ag, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE.... Telineasennus, Kotelo: 1U



Management features		Design	
Switch type *	Managed	LED indicators	✓
Switch layer	L3	Number of fans	2 fan(s)
Quality of Service (QoS) support	✓	Safety	cUL, CB, CE, CCC, BSM
Web-based management	✓	Electromagnetic compatibility	CE, FCC Class A, C-Tick, VCCI, BSMI, CCC
Traffic classification	✓	Performance	
ARP inspection	✓	Virtual stacking (units)	32
System event log	✓	Noise level	53.9 dB
Ports & interfaces		Mean time between failures (MTBF)	263936 h
Basic switching RJ-45 Ethernet ports quantity *	44	Power	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included *	✓
Gigabit Ethernet (copper) ports quantity	44	Redundant power supply (RPS) support	✓
Combo SFP ports quantity	4	Number of power supply units	1
SFP+ module slots quantity	4	AC input voltage	100 - 240 V
Console port	RJ-45/Mini-USB	AC input frequency	50 - 60 Hz
USB 2.0 ports quantity	1	Power consumption (max)	62 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qbb, IEEE 802.1ag, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✗
10G support *	✓	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operating temperature (T-T)	-5 - 50 °C
Port mirroring	✓	Storage temperature (T-T)	-40 - 70 °C
Full duplex	✓	Operating relative humidity (H-H)	10 - 95%
Flow control support	✓	Storage relative humidity (H-H)	5 - 95%
Link aggregation	✓	Heat dissipation	212 BTU/h
Broadcast storm control	✓	Weight & dimensions	
Spanning tree protocol	✓	Width	441 mm
VLAN support	✓	Depth	260 mm
Virtual LAN features	Stacked VLAN, Private VLAN, Tagged VLAN, Port-based VLAN	Height	44 mm
		Weight	4.04 kg
		Packaging data	
		Package width	538 mm
		Package depth	560 mm
		Package height	170 mm
		Package weight	5.55 kg

Network		Technical details	
Number of VLANs	4094	Shipping (inner) case height	57.2 cm
Data transmission		Shipping (inner) case width	36.2 cm
Switching capacity *	176 Gbit/s	Shipping (inner) case length	57.9 cm
Throughput	130.95 Mpps	Shipping (inner) case net weight	14.3 kg
MAC address table *	68000 entries	Products per shipping (inner) case	3 pc(s)
Number of queues	8	Pallet gross weight (air)	578.3 kg
Number of IP interfaces	256	Master (outer) cases per pallet (air)	32 pc(s)
Jumbo frames support	✓	Products per pallet (air)	96 pc(s)
Jumbo frames	12000	Pallet gross length	110 cm
Packet buffer memory	4 MB	Pallet gross width	120 cm
Security		Pallet height (air)	193.5 cm
DHCP features	DHCP server, DHCP client	Pallet gross weight (sea)	578.3 kg
Access Control List (ACL)	✓	Master (outer) cases per pallet (sea)	32 pc(s)
IGMP snooping	✓	Products per pallet (sea)	96 pc(s)
Security algorithms	802.1x RADIUS, SSH, SSH-2, SSL/TLS	Pallet height (sea)	193.5 cm
MAC address filtering	✓	Shipping (inner) case gross weight	17.5 kg
SSH/SSL support	✓	Logistics data	
Loop protection	✓	Harmonized System (HS) code	85176990
BPDU filtering/protection	✓		
Authentication	Guest VLAN, Port-based authentication		
Multicast features			
Multicast support	✓		
Protocols			
Management protocols	SNMP, NTPv3/v4, Telnet		
Design			
Rack mounting *	✓		
Stackable *	✓		
Form factor	1U		
Product colour	Black		



0790069425615



790069425615

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.