

## D-Link DGS-1510-28XMP verkkokytkin Hallittu L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta, Harmaa

**Tuotemerkki** : D-Link

**Tuotekoodi**: DGS-1510-28XMP

**Tuotteen nimi** : DGS-1510-28XMP

D-Link DGS-1510-28XMP. Kytkin tyyppi: Hallittu, Kytinkerros: L2/L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 16384 entries, Kytkentäkapasiteetti: 128 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Power over Ethernet -tuki. Telineasennus



Management features		Design	
Switch type *	Managed	Safety	cUL, CB
Switch layer	L2/L3	<b>Performance</b>	
Quality of Service (QoS) support	✓	Physical stacking (units)	6
Traffic classification	✓	Virtual stacking (units)	32
System event log	✓	Noise level	56.9 dB
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	24	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input frequency	50 - 60 Hz
SFP+ module slots quantity	4	Power consumption (max)	436.3 W
Fiber optic connector	SFP+	<b>Power over Ethernet (PoE)</b>	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x	Power over Ethernet (PoE) ports quantity	24
	10G support *	Power over Ethernet (PoE) power per port	30 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Total Power over Ethernet (PoE) budget	370 W
Cable types supported	Cat5, Cat5e	Operational conditions	
Port mirroring	✓	Operating temperature (T-T)	-5 - 50 °C
Full duplex	✓	Storage temperature (T-T)	-20 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	0 - 95%
Link aggregation	✓	Storage relative humidity (H-H)	0 - 95%
Broadcast storm control	✓	Heat dissipation	1487.78 BTU/h
Auto MDI/MDI-X	✓	Weight & dimensions	
Spanning tree protocol	✓	Width	440 mm
Head-of-line (HOL) blocking	✓	Depth	308 mm
Auto-negotiation	✓	Height	44 mm
MAC address auto-learning supported	✓	Weight	4.25 kg
VLAN support	✓	Packaging data	
Virtual LAN features	Tagged VLAN, Protocol-based VLAN	Package width	450 mm
Number of VLANs	4094	Package depth	510 mm
		Package height	121 mm
		Package weight	7.06 kg
		Technical details	
		Shipping (inner) case height	48.5 cm

Data transmission		Technical details	
Switching capacity *	128 Gbit/s	Shipping (inner) case width	38.5 cm
Throughput	95.24 Mpps	Shipping (inner) case length	53 cm
MAC address table *	16384 entries	Shipping (inner) case net weight	14.3 kg
Store-and-forward	✓	Products per shipping (inner) case	3 pc(s)
Number of queues	8	Pallet gross weight (air)	561.6 kg
Jumbo frames support	✓	Master (outer) cases per pallet (air)	24 pc(s)
Jumbo frames	9216	Products per pallet (air)	72 pc(s)
Packet buffer memory	1.5 MB	Pallet gross length	110 cm
Security		Pallet gross width	120 cm
DHCP features	DHCP server, DHCP client	Pallet height (air)	2.08 m
Access Control List (ACL)	✓	Pallet gross weight (sea)	561.6 kg
Access Control List (ACL) rules	768	Master (outer) cases per pallet (sea)	24 pc(s)
IGMP snooping	✓	Products per pallet (sea)	72 pc(s)
Security algorithms	802.1x RADIUS, EAP, SNMP, SSH, SSH-2, SSL/TLS	Pallet height (sea)	2.08 m
SSH/SSL support	✓	Shipping (inner) case gross weight	22.6 kg
BPDU filtering/protection	✓	Certificates	
Authentication	MAC-based authentication, Port-based authentication	Certification	CE, FCC, C-Tick, VCCI, BSMI, CCC
Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990
Design			
Rack mounting *	✓		
Stackable *	✓		
Product colour	Black, Grey		
LED indicators	Activity, Link, PoE, Power, Speed		
Number of fans	2 fan(s)		



0790069413780



790069413780

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.