
## D-Link

## D-Link DES-1008PA verkkokytkin Hallitsematon Fast Ethernet (10/100) Power over Ethernet -tuki musta

Tuotemerkki : D-Link Tuotekoodi: DES-1008PA

Tuotteen nimi: DES-1008PA







Management features		Operational conditions	
Switch type *	Unmanaged	Operating relative humidity (H-H)	10 - 95%
Ports & interfaces		Storage relative humidity (H-H)	5 - 90%
Basic switching RJ-45 Ethernet ports quantity *	8	Weight & dimensions Width	170.2 mm
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Depth	99.1 mm
Fast Ethernet (copper) ports quantity	8	Height Weight	27.9 mm 454 g
Network		Packaging data	
Networking standards *  10G support *	IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x	Package width Package depth Package height	208 mm 250 mm 68 mm
Full duplex	·	Package weight	1.19 kg
Half duplex	<b>✓</b>	Technical details	
Flow control support Auto MDI/MDI-X	<b>,</b>	Shipping (inner) case height Shipping (inner) case width Shipping (inner) case length	43 cm 26.5 cm 37.5 cm
Data transmission		Shipping (inner) case net weight	11.9 kg
Switching capacity * MAC address table *	1.6 Gbit/s 1000 entries	Products per shipping (inner) case Pallet gross weight (air)	10 pc(s) 628.5 kg
Store-and-forward	<b>✓</b>	Master (outer) cases per pallet (air)	48 pc(s)
Maximum data transfer rate Packet buffer memory	1 Gbit/s 0.09 MB	Products per pallet (air) Pallet gross length	480 pc(s) 110 cm
Design		Pallet gross width	120 cm
Product colour LED indicators Safety	Black LAN, PoE, Power LVD	Pallet height (air) Pallet gross weight (sea) Master (outer) cases per pallet (sea) Products per pallet (sea)	191.5 cm 628.5 kg 48 pc(s) 480 pc(s)
Power		Pallet height (sea)	191.5 cm
Power source *	DC	Shipping (inner) case gross weight	12.7 kg
Input current Input voltage	1.25 A 51 V	Certificates	
Power over Ethernet (PoE)		Certification	FCC, CE, VCCI
Power over Ethernet (PoE) *	<b>✓</b>	Logistics data	
Power over Ethernet (PoE) ports quantity	4	Harmonized System (HS) code	85176990

Power over Ethernet (PoE)	
Power over Ethernet (PoE) power per port	15 W
Total Power over Ethernet (PoE) budget	52 W
Operational conditions	
Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -10 - 70 °C















Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.