APC

APC SMT1500IC UPS-virtalähde Linjainteraktiivinen 1,5 kVA 1000 W 8 AC-pistorasia(a)

Tuotemerkki : APC   **Tuotekoodi:** SMT1500IC

**Tuotteen nimi :** SMT1500IC

APC SMT1500IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 1000 W. Pistorasian tyypit: C13 liitin, IEC Jumpers, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Johdon pituus: 1,83 m. Tuotteen leveys: 171 mm, Tuotteen syvyys: 439 mm, Tuotteen korkeus: 219 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	1.5 kVA
Output power *	1000 W
Waveform *	Sine
Input operation voltage (min) *	151 V
Input operation voltage (max) *	302 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	459 J
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	45 dB
Surge protection	✔
Audible alarm(s)	✔
Web-based management	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	✔
Temperature voltage compensation	✔

Ports & interfaces

AC outlet types	C13 coupler, IEC Jumpers
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)

Battery

Battery recharge time	3 h
Hot-swap battery	✔
Automatic battery test	✔
Cold start	✔

Design

Form factor *	Mini Tower
Cable length	1.83 m
Product colour *	Black
Display type	LCD
LED indicators	✔
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Sustainability certificates	Green Premium
Compliance certificates	RoHS

Weight & dimensions

Width	171 mm
Depth	439 mm

Ports & interfaces

USB port	✔
USB 2.0 ports quantity	1
Serial interface	✔
Serial interface type	RS-232
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery life (max)	5 year(s)

Weight & dimensions

Height	219 mm
Weight	24.1 kg
Package width	328 mm
Package depth	595 mm
Package height	376 mm
Package weight	27.2 kg

Packaging data

Cables included	RS-232, USB cable
Quick installation guide	✔
Resource CD	✔
Software CD	✔

Logistics data

Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000

0731304332992

731304332992