

APC SMT1000IC UPS-virtalähde Linjainteraktiivinen 1 kVA 700 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMT1000IC

Tuotteen nimi : SMT1000IC

APC SMT1000IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 700 W. Pistorasian tyypit: C13 liitin, IEC Jumpers, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 171 mm, Tuotteen syvyys: 439 mm, Tuotteen korkeus: 219 mm





Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	1 kVA	Battery recharge time	3 h
Output power *	700 W	Hot-swap battery	1
Waveform *	Sine	Automatic battery test	1
Input operation voltage (min) *	151 V	Cold start	1
Input operation voltage (max) st	302 V	Replacement battery cartridge	RBC6
Input frequency *	50/60 Hz	Design	
Output operation voltage (min)	220 V	5	
Output operation voltage (max)	240 V	Form factor *	Mini Tower
Output frequency	50/60 Hz	Product colour *	Black
Automatic Voltage Regulation (AVR)	 Image: A second s	Display type	LCD
Surge energy rating	459 J	LED indicators	4
Response time Output voltage Total Harmonic	10 ms	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778,
Distortion (THD)	5%		VDE, REACH
Noise level	41 dB	Operational conditions	
Surge protection	1	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	1	Storage temperature (T-T)	-15 - 45 °C
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 95% 0 - 95%
Auto-restart	1	Operating altitude	0 - 3000 m
Temperature voltage compensation	1	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, IEC Jumpers	Sustainability certificates	Green Premium
Power plug	C14 coupler	Compliance certificates	RoHS
AC outlets quantity	8 AC outlet(s)		
USB port	1		

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Width	171 mm
USB port type	USB Type-A	Depth	439 mm
Serial interface	1	Height	219 mm
Serial ports quantity	1	Weight	18.9 kg
Ethernet LAN (RJ-45) ports	1	Package width	328 mm
SmartSlot	1	Package depth	595 mm
Detter		Package height	376 mm
Battery		Package weight	22.8 kg

Battery technology

Sealed Lead Acid (VRLA)

Quick installation guide


Packaging data

Cables included

Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000

RJ-45, USB cable

.





731304332978

0731304332978

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.