



APC Smart-UPS SMC1500IC - 8x C13, USB, SmartConnect, 1500VA

Brand : APC

Product code: SMC1500IC

Product name : APC Smart-UPS SMC1500IC - 8x C13, USB, SmartConnect, 1500VA

- 1500VA/900W line interactive pure sine wave tower UPS
- Ideal for entry-level servers, networks, retail POS, business VOIP and desktops
- Automatic Voltage Regulation keeps output voltage within acceptable user selectable levels
- Cloud-based remote power monitoring via SmartConnect Ethernet Port
- Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown

APC Smart-UPS SMC1500IC - 8x C13, USB, SmartConnect, 1500VA

APC Smart-UPS SMC1500IC - 8x C13, USB, SmartConnect, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 171 mm, Depth: 439 mm, Height: 219 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	1.5 kVA	Battery recharge time	3 h
Output power *	900 W	Hot-swap battery	✓
Waveform *	Sine	Automatic battery test	✓
Input operation voltage (min) *	170 V	Cold start	✓
Input operation voltage (max) *	300 V		
Input frequency *	50/60 Hz	Design	
Output operation voltage (min)	220 V	Form factor *	Mini Tower
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Automatic Voltage Regulation (AVR)	✓	LED indicators	✓
Surge energy rating	459 J	Certification	C-tick, CE, CSA, GOST, UL 1778, VDE
Output voltage Total Harmonic Distortion (THD)	5%	Operational conditions	
Noise level	45 dB	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	✓	Storage temperature (T-T)	-15 - 45 °C
Web-based management	✓	Operating relative humidity (H-H)	0 - 95%
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Storage relative humidity (H-H)	0 - 95%
Auto-restart	✓	Operating altitude	0 - 3000 m
Temperature voltage compensation	✓	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler	Sustainability certificates	Green Premium
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	8 AC outlet(s)	Width	171 mm
USB port	✓	Depth	439 mm
USB 2.0 ports quantity	1	Height	219 mm
Serial interface	✓	Weight	24.1 kg
Serial ports quantity	1	Package width	328 mm
		Package depth	595 mm
		Package height	376 mm

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	USB cable
Number of batteries supported	1	Resource CD	✓
		Software CD	✓
		Package volume	27230 cm ³
Logistics data			
		Products per pallet	18 pc(s)
		Harmonized System (HS) code	85078000



0731304332961



731304332961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-NOV-2024. Prints or copies of Information are only valid on the printed Publication date