




## APC SMC1500IC UPS-virtalähde Linjainteraktiivinen 1,5 kVA 900 W 8 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SMC1500IC

**Tuotteen nimi :** SMC1500IC

APC SMC1500IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 171 mm, Tuotteen syvyys: 439 mm, Tuotteen korkeus: 219 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	1.5 kVA	Battery recharge time	3 h
Output power *	900 W	Hot-swap battery	✓
Waveform *	Sine	Automatic battery test	✓
Input operation voltage (min) *	170 V	Cold start	✓
Input operation voltage (max) *	300 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	459 J		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	45 dB		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	✓		
Temperature voltage compensation	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Mini Tower
Power plug	C14 coupler	Product colour *	Black
AC outlets quantity	8 AC outlet(s)	Display type	LCD
USB port	✓	LED indicators	✓
		Certification	C-tick, CE, CSA, GOST, UL 1778, VDE
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	171 mm
		Depth	439 mm

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Height	219 mm
Serial interface	✓	Weight	24.1 kg
Serial ports quantity	1	Package width	328 mm
<b>Battery</b>		Package depth	595 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	376 mm
Number of batteries supported	1	<b>Packaging data</b>	
		Cables included	USB cable
		Resource CD	✓
		Software CD	✓
		Package volume	27230 cm <sup>3</sup>
		<b>Logistics data</b>	
		Products per pallet	18 pc(s)
		Harmonized System (HS) code	85078000



0731304332961



731304332961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.