



## APC Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD



Brand : APC

Product code: SMC1500I-2UC

Product name : Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD



- 1500VA/900W line interactive pure sine wave 2U rackmount UPS
  - Ideal for entry-level servers, networks, retail POS, and business VOIP
  - Automatic Voltage Regulation keeps output voltage within acceptable user selectable levels
  - Cloud-based remote power monitoring via SmartConnect Ethernet Port
  - Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown
- Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD


Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	1.5 kVA	Automatic battery test	✓
Output power *	900 W	Cold start	✓
Waveform *	Sine	<b>Design</b>	
Input operation voltage (min) *	170 V	Form factor *	Rackmount
Input operation voltage (max) *	300 V	Rack capacity	2U
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Certification	C-tick, CE, CSA, GOST, UL 1778, VDE
Automatic Voltage Regulation (AVR)	✓	<b>Operational conditions</b>	
Surge energy rating	459 J	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	5%	Storage temperature (T-T)	-15 - 45 °C
Noise level	46 dB	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Web-based management	✓	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Non-operating altitude	0 - 15000 m
Auto-restart	✓	<b>Technical details</b>	
Temperature voltage compensation	✓	Sustainability certificates	Green Premium
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
AC outlet types	C13 coupler	Width	432 mm
Power plug	C14 coupler	Depth	477 mm
AC outlets quantity	4 AC outlet(s)	Height	86 mm
USB port	✓	Weight	28.6 kg
USB 2.0 ports quantity	1	Package width	594 mm
Serial interface	✓	Package depth	603 mm
Serial interface type	RJ-45	Package height	251 mm
<b>Battery</b>		Package weight	31.9 kg
Battery technology	Sealed Lead Acid (VRLA)	<b>Packaging data</b>	
Battery life (max)	6 year(s)	Rack mount kit	✓
Battery recharge time	3 h	Cables included	USB cable
		Quick installation guide	✓
		Resource CD	✓
		Software CD	✓
		<b>Logistics data</b>	
		Products per pallet	16 pc(s)

**Logistics data**

Harmonized System (HS) code 85078000



0731304332954



731304332954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date