

## APC Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

Brand : APC

Product code: SMC1000IC

**Product name :** Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

- 1000VA/600W line interactive pure sine wave tower  $\ensuremath{\mathsf{UPS}}$ 

- Ideal for entry-level servers, networks, retail POS, business VOIP and desktops

- Automatic Voltage Regulation keeps output voltage within acceptable user selectable levels

- Cloud-based remote power monitoring via SmartConnect Ethernet Port

- Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown

Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD





| Features   |   | Battery  |   |
|--|---|--|---|
| UPS topology *<br>Output power capacity *<br>Output power *<br>Waveform *<br>Input operation voltage (min) *<br>Input operation voltage (max) *<br>Input frequency *<br>Output operation voltage (min) | Line-Interactive<br>1 kVA<br>600 W<br>Sine<br>170 V<br>300 V<br>50/60 Hz<br>220 V | Battery life (max)<br>Battery recharge time<br>Hot-swap battery<br>Automatic battery test<br>Cold start<br><b>Design</b><br>Form factor *              | 5 year(s)<br>3 h<br>J   J < |
| Output operation voltage (max)<br>Output frequency<br>Automatic Voltage Regulation (AVR)<br>Surge energy rating  | 240 V<br>50/60 Hz<br>✔<br>455 J   | Product colour *<br>Display type<br>LED indicators<br>Certification  | Black<br>LCD<br>✔<br>CE, CSA, GOST, UL 1778, VDE  |
| Output voltage Total Harmonic<br>Distortion (THD)  | 5%  | Operational conditions   |   |
| Noise level<br>Surge protection<br>Audible alarm(s)<br>Web-based management  | 41 dB<br>✓<br>✓<br>Alarm when on battery, Low battery                             | Operating temperature (T-T)<br>Storage temperature (T-T)<br>Operating relative humidity (H-H)<br>Storage relative humidity (H-H)<br>Operating altitude | 0 - 40 °C<br>-15 - 45 °C<br>0 - 95%<br>0 - 95%<br>0 - 3000 m  |
| Audible alarm modes<br>Auto-restart  | alarm, Overload alarm   | Non-operating altitude Technical details   | 0 - 15000 m   |
| Temperature voltage compensation   | ·   | Sustainability certificates  | Green Premium   |
| Ports & interfaces   |   | Weight & dimensions  |   |
| AC outlet types<br>Power plug<br>AC outlets quantity   | C13 coupler<br>C14 coupler<br>8 AC outlet(s)                                      | Width<br>Depth<br>Height   | 171 mm<br>439 mm<br>219 mm  |

| Ports & interfaces         |                         | Weight & dimensions |   |  |
|----------------------------|-------------------------|---------------------|---|--|
| USB port                   | v                       | Weight              | 17.3 kg   |  |
| USB 2.0 ports quantity     | 1                       | Package width       | 328 mm  |  |
| Serial ports quantity      | 1                       | Package depth       | 595 mm  |  |
| Ethernet LAN (RJ-45) ports | 1                       | Package height      | 376 mm  |  |
| Battery                    |                         | Package weight      | 19.6 kg   |  |
| Battery technology         | Sealed Lead Acid (VRLA) | Packaging data      | Packaging data  |  |
|                            |                         | Cables included     | USB cable   |  |
|                            |                         | Resource CD         | ✓   |  |
|                            |                         | Software CD         | <ul> <li>Image: A set of the set of the</li></ul> |  |
|                            |                         | Logistics data      |   |  |

Products per pallet

Harmonized System (HS) code

18 pc(s)

85078000

## Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date





731304332947

0731304332947

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.