



## APC SMC1000I-2UC UPS-virtalähde Linjainteraktiivinen 1 kVA 600 W 4 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SMC1000I-2UC

**Tuotteen nimi :** SMC1000I-2UC

APC SMC1000I-2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 600 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a).  
Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 6 vuosi/vuosisia, Akun latausaika: 3 h.  
Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 406 mm, Tuotteen korkeus: 86 mm

| Features  |  | Battery                           |   |
|---|--|-----------------------------------|---|
| UPS topology *                                  | Line-Interactive   | Battery recharge time             | 3 h   |
| Output power capacity *                         | 1 kVA  | Replacement battery cartridge     | APCRBC124   |
| Output power *                                  | 600 W  | <b>Design</b>                     |   |
| Waveform *                                      | Sine   | Form factor *                     | Rackmount   |
| Input operation voltage (min) *                 | 170 V  | Rack capacity                     | 2U  |
| Input operation voltage (max) *                 | 300 V  | Cable length                      | 2.44 m  |
| Input frequency *                               | 50/60 Hz   | Product colour *                  | Black   |
| Output operation voltage (min)                  | 220 V  | Display type                      | LCD   |
| Output operation voltage (max)                  | 240 V  | Certification                     | CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH |
| Output frequency                                | 50/60 Hz   | <b>Operational conditions</b>     |   |
| Automatic Voltage Regulation (AVR)              | ✓  | Operating temperature (T-T)       | 0 - 40 °C   |
| Surge energy rating                             | 680 J  | Storage temperature (T-T)         | -15 - 45 °C   |
| Output voltage Total Harmonic Distortion (THD)  | 5%   | Operating relative humidity (H-H) | 0 - 95%   |
| Noise level                                     | 41 dB  | Storage relative humidity (H-H)   | 0 - 95%   |
| Surge protection                                | ✓  | Operating altitude                | 0 - 3000 m  |
| Audible alarm(s)                                | ✓  | Non-operating altitude            | 0 - 15000 m   |
| Audible alarm modes                             | Alarm when on battery, Low battery alarm, Overload alarm | <b>Technical details</b>          |   |
| <b>Ports &amp; interfaces</b>                   |  | Sustainability certificates       | ENERGY STAR, Green Premium  |
| AC outlet types                                 | C13 coupler  | Compliance certificates           | RoHS  |
| Power plug                                      | C14 coupler  | <b>Weight &amp; dimensions</b>    |   |
| AC outlets quantity                             | 4 AC outlet(s)   | Width                             | 432 mm  |
| Number of outlets (Battery backup & protection) | 4  | Depth                             | 406 mm  |
| USB port  | ✓  | Height                            | 86 mm   |
| USB 2.0 ports quantity                          | 1  | Weight                            | 20.5 kg   |
| Serial interface                                | ✓  | Package width                     | 535 mm  |
| Serial interface type                           | RS-232   | Package depth                     | 570 mm  |
| Ethernet LAN (RJ-45) ports                      | 1  | Package height                    | 235 mm  |
| SmartSlot                                       | ✓  | Package weight                    | 20.7 kg   |
| <b>Battery</b>                                  |  | <b>Packaging data</b>             |   |
| Battery technology                              | Sealed Lead Acid (VRLA)                                  | Rack mount kit                    | ✓   |
| Number of batteries supported                   | 1  | Cables included                   | RJ-45, RS-232   |
| Battery life (max)                              | 6 year(s)  | Resource CD                       | ✓   |
|   |  | Software CD                       | ✓   |
|   |  | <b>Logistics data</b>             |   |
|   |  | Products per pallet               | 16 pc(s)  |
|   |  | Harmonized System (HS) code       | 85078000  |



0731304332930



731304332930

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.