

APC PDUM160H-B power distribution unit (PDU)

Brand : APC Product code: PDUM160H-B

Product name: PDUM160H-B

nfraStruXure Modular IT Power Distribution Unit w/36 Poles, MBP & Batt. Frame for 9 Modules, 400V

APC PDUM160H-B power distribution unit (PDU):

InfraStruXure Central compatible

 ${\bf Enables} \ {\bf centralized} \ {\bf management} \ {\bf via} \ {\bf APC} \ {\bf InfraStruXure} \\ {\bf @} \ {\bf Central}.$

Smallest footprint

Minimizes your real estate expenses

Top and bottom cable entry (standard)

Flexibility that allows the customer to decide - and at no extra cost.

UL-listed Touch-safe backplane

Adding Power Distribution Modules requires no hot work; one trained user can safely add new modules without removing power to the existing PDU load

Multiple distribution options

Superior design flexibility enables a wide range of customer requirements to be addressed.

Toolless installation of breakers

Install factory-assembled Power Distribution Modules in under ten minutes - no tools are required

Safety

Enhance user safety with isolation at all touch points and with positive locking mechanisms that reduce the risk of accidental disconnection





| Ports & interfaces | | Weight & dimensions | |
|---------------------------------|------------------------------------|-----------------------------------|----------------------|
| Input connection type | Hard Wire 5-wire (3PH $+$ N $+$ G) | Weight | 411.8 kg |
| Output connections | 2x Hard Wire 5-wire (3PH + N + G) | Packaging data | |
| Features | | Package dimensions (WxDxH) | 848 x 1210 x 2150 mm |
| Certification | CE, FCC 15 A | Package weight | 444.6 kg |
| Power | | Operational conditions | |
| Nominal input voltage * | 400 V | Operating temperature (T-T) | 0 - 40 °C |
| Load capacity | 160000 VA | Storage temperature (T-T) | -15 - 40 °C |
| Maximum input current per phase | 295 A | Operating relative humidity (H-H) | 0 - 95% |
| Weight & dimensions | | Storage relative humidity (H-H) | 0 - 95% |
| Dimensions (WxDxH) | 600 x 1070 x 1991 mm | | |





731304257608

0731304257608

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.